

**CMSC 430**  
**Introduction to Compilers**  
Fall 2016

---

**Everything (else) you always wanted to know about OCaml (but were afraid to ask)**

# OCaml

---

- You know it well from CMSC 330
- All programming projects will be in OCaml
  - OCaml is well-designed for building language tools
- In 330, we covered all the basics
  - Tuples, lists, recursion, pattern matching, higher-order functions, currying, data types, modules, module types, updatable references
- For larger projects, there's more to know

# Records

---

- Labeled tuples of values

```
# type course = {title:string; num:int};;
type course = { title : string; num : int; }
# let x = {title="Intro to Compilers"; num=430};;
val x : course = {title = "Intro to Compilers"; num = 430}
```

- Fields are referenced with the dot notation

```
# x.title;;
- : string = "Introduction to Compilers"
# x.number;;
- : int = 430
```

- All record types are named, and must be complete in any instance

```
# let y = {title="Intro to Compilers"};;
Error: Some record field labels are undefined: num
```

# Records (cont'd)

---

- Record patterns can include partial matches

```
# let nextNum {num=x} = x;;  
val nextNum : course -> int = <fun>
```

- The `with` construct can be used to modify just part of a record

```
# {x with num=431};;  
- : course = {title = "Intro to compilers"; num = 431}
```

# Records (cont'd)

---

- Record fields may be **mutable**

```
# type course = {title:string; mutable num:int};;
type course = { title : string; mutable num : int; }
# let x = {num=430; title="Intro to compilers"};;
val x : course = {title = "Intro to compilers"; num = 430}
# x.num <- 431;;
- : unit = ()
# x;;
- : course = {title = "Intro to compilers"; num = 431}
```

- In fact, this is what updatable refs translate to

```
# let y = ref 42;;
val y : int ref = {contents = 42}
```

# Arrays and strings

---

- OCaml arrays are mutable and bounds-checked

```
# let x = [|1;2;3|];;
val x : int array = [|1; 2; 3|]
# x.(0) <- 4;;
- : unit = ()
# x;;
- : int array = [|4; 2; 3|]
# x.(4);;
Exception: Invalid_argument "index out of bounds".
# x.(-1);;
Exception: Invalid_argument "index out of bounds".
```

- OCaml strings are also mutable (this will change!)

```
# let x = "Hello";;
val x : string = "Hello"
# x.[0] <- 'J';;
- : unit = ()
# x;;
- : string = "Jello"
```

# Design discussion

---

- OCaml has several similar constructs
  - Tuples
  - Lists
  - Records
  - Arrays
  - Data types
- Why have all these choices? Do other languages (e.g., Ruby) have all these different constructs?

# Labeled arguments

---

- OCaml allows arguments to be labeled

```
# let f ~x ~y = x-y;;  
val f : x:int -> y:int -> int = <fun>  
# f 4 3;;  
- : int = 1  
# f ~y:4 ~x:3;;  
- : int = -1
```

- Functions with labeled args can be partially applied

```
# let g = f ~y:4;;  
val g : x:int -> int = <fun>  
# g 3;;  
- : int = -1  
# g ~x:3;;  
- : int = -1
```

# Optional arguments

---

- Labeled arguments may be optional

```
# let bump ?(step = 1) x = x + step;;  
val bump : ?step:int -> int -> int = <fun>  
# bump 2;;  
- : int = 3  
# bump ~step:3 2;;  
- : int = 5
```

- One nit: type inference with partial applications of functions with labeled arguments may not always work

# While and for

---

```
# while true do Printf.printf "Hello\n";;  
Hello  
Hello  
Hello  
...  
# for i = 1 to 10 do Printf.printf "%d\n" i done;;  
1  
2  
...  
10
```

- Can you encode **while** and **for** only using functions and recursion?

# Modules

---

```
module type SHAPES =
  sig
    type shape
    val area : shape -> float
    val unit_circle : shape
    val make_circle : float -> shape
    val make_rect : float -> float -> shape
  end;;

module Shapes : SHAPES =
  struct
    ...
    let make_circle r = Circle r
    let make_rect x y = Rect (x, y)
  end
```

# Functors

---

- Modules can take other modules as arguments
  - Such a module is called a *functor*

```
module type OrderedType = sig
  type t
  val compare : t -> t -> int
end

module Make(Ord: OrderedType) =
struct ... end

module StringSet = Set.Make(String) ;;
(* works because String has type t, implements compare *)
```

- Other examples: Hashtbl, Map, Queue, Stack

# Variants

---

- Recall OCaml data types (also called *variants*)

```
type shape =  
| Circle of float  
| Rect of float * float
```

- Each constructor name refers to a unique type
  - E.g., **Circle** always makes a shape
- Some downsides
  - Have to define all such types in advance of uses
  - Can't accept data coming from two different variants

# Polymorphic variants

- Like variants, but permit an unbounded number of constructors, created anywhere
  - Type inference takes care of matching up various uses

```
# [\On; \Off];;  
- : [> \Off | \On ] list = [\On; \Off]  
# \Number 1;  
- : [> \Number of int ] = \Number 1  
# let f = function \On -> 1 | \Off -> 0 | \Number n -> n;;  
val f : [< \Number of int | \Off | \On ] -> int = <fun>  
# List.map f [\On; \Off];;  
- : int list = [1; 0]
```

- “<”—allow fewer tags      “>”—allow more tags
- Can remove this ability by creating a named type

```
# type 'a vlist = [\Nil | \Cons of 'a * 'a vlist];;  
type 'a vlist = [ \Cons of 'a * 'a vlist | \Nil ]
```

# Regular vs. polymorphic variants

---

- Benefits of polymorphic variants:
  - More flexible
  - If used well, can improve modularity, maintainability
- Benefits of regular variants:
  - More type checking permitted
    - Only declared constructors used
    - Check for complete pattern matching
    - Enforce type constraints on parameters
  - Better error messages
    - Sometimes type inference with polymorphic variants subtle
  - Compiler can create slightly more optimized code
    - More is known at compile time

# A note on OCaml versions

---

- We will use version 4.03.0
  - Add the following directory to your path:

`/afs/glue.umd.edu/class/fall2016/cmsc/430/0101/public/bin`

    - Ask a TA (and be a bit embarrassed!) if you don't know how
  - This version should be installed on submit now
- If you are installing OCaml yourself, we recommend using [opam](#)
  - We'll also use the [ounit](#) and [Yojson](#) packages
    - They are installed on GRACE at the path above