

CMSC330 Fall 2015 Midterm #1

12:30pm/2:00pm/5:00pm

Name: _____

Discussion Time:	10am	11am	12pm	1pm	2pm	3pm
TA Name (Circle):	Adam Amelia	Maria Amelia	Chris Samuel	Chris Josh	Michael Max	Candice

Instructions

- Do not start this test until you are told to do so!
- You have 75 minutes to take this midterm.
- This exam has a total of 100 points, so allocate 45 seconds for each point.
- This is a closed book exam. No notes or other aids are allowed.
- Answer short-answer questions concisely in 2-3 sentences. Longer answers are not needed.
- For partial credit, show all of your work and clearly indicate your answers.
- Write neatly. Credit cannot be given for illegible answers.

	Problem	Score
	PL Concepts	/13
	Ruby Regular Expressions	/10
	Ruby Execution	/18
	Ruby Programming	/14
	OCaml Typing	/15
	OCaml Execution	/15
	OCaml Programming	/15
	Total	/100

1. Programming Language Concepts (13 pts)

- a) (3 pts) What is the difference between *dynamic typing* and *type inference*?
- b) (3 pts) What is the key difference between a *function pointer* and a *closure*?
- c) (2 pts) True or False: *Static typing* is compatible with *implicit declarations*.
- d) (3 pts) Multiple choice: What do we mean when we refer to *first-class functions*?
- a. These are functions that are implemented using objects; i.e., they have a class
 - b. First-class functions have the same status as other data, i.e., they can be created in and returned from (other) functions, and stored in data structures
 - c. These are functions that encode an object
 - d. These are things like Ruby code blocks
- e) (2 pts) Suppose we have a variable `x` of type `int ref`. Circle those statements below that are true (you may circle either, neither, or both):
- 1) `x` is immutable
 - 2) the storage that `x` points to is immutable

2. Ruby Regular Expressions (10 pts)

a. (3 pts) Give an English description of the strings matched by Ruby regexp `C?[msc]*330`

b. (4 pts) Circle which of the following strings matches the Ruby regexp `[aeiou][0-9]+$`

"who13"

"o123o"

"a2"

"cm330"

c. (3 pts) Give a Ruby regexp that denotes the language of strings with any number of a's and an odd number of b's

3. Ruby Execution (18 pts)

To the write of each Ruby code snippet below, indicate what happens when you run the code. If there is a run-time error write *FAIL*; otherwise, write what is printed out. Assume that the `nil` object prints as `"(nil)"` (and not the empty string).

a) (4 pts)

```
h = { 1 => "CS", 2 => "Math" }  
h.keys.each{ |x| puts "#{h[x]}" }
```

b) (3 pts)

```
a = Array.new  
a[1] = 0  
puts a["hello"]
```

c) (3 pts)

```
a = [ ]  
a[3] = 2  
puts a
```

d) (4 pts)

```
ws = "1.23 4 hello fred"  
x, y, z = ws.split(/\s/)  
puts x+y
```

e) (4 pts)

```
class Thing  
  @@things = 0  
  def initialize(name)  
    @name = name  
    @@things += 1  
  end  
  def self.get_things  
    return @@things  
  end  
end  
Thing.new("thing20");  
Thing.new("thing6")  
puts Thing.get_things
```

4. Ruby Programming (14 pts)

On the next page is the initial Ruby implementation of a class `Set`, which implements a collection of distinct elements. This implementation contains a constructor (`initialize`) and method `add`. Add implementations of **any two of the following three functions** (7 pts each)

- `member?(x)` returns true if `x` is in the set, false otherwise
- `elems` returns a copy of the contents of the set as an array (order doesn't matter)
- `union(x)` returns a new set that contains all the elements in the receiving set and the elements in `x`

For full credit, do not change the existing methods or add methods beyond those required of you. If you can't figure it out without such changes, you can make them for partial credit.

Here is an IRB session with the class.

```
>> s1 = Set.new
=> #<Set:0x007fd0f38f5608 @s={}>

>> s1.add(1).add(1)
=> #<Set:0x007fd0f38f5608 @s={1=>true}>

>> s1.member?(1)
=> true

>> s2 = Set.new
=> #<Set:0x007fd0f38ffbf8 @s={}>

>> s2.add(1).add(2).add(2).elems
=> [1, 2]

>> s3 = Set.new
=> #<Set:0x007fd0f390f788 @s={}>

>> s3.add(3).add(4).add(2)
=> #<Set:0x007fd0f390f788 @s={3=>true, 4=>true, 2=>true}>

>> s4 = s1.union(s3)
=> #<Set:0x007fd0f503b100 @s={1=>true, 3=>true, 4=>true, 2=>true}>

>> s4.elems
=> [1, 3, 4, 2]
```

Answer to problem 4:

```
class Set
```

```
  def initialize
```

```
    @s = { }
```

```
  end
```

```
  def add(x)
```

```
    @s[x] = true
```

```
    return self
```

```
  end
```

```
  # put your member?, elems, and/or union methods below
```

```
end
```

5. OCaml Typing (15 pts)

a) (3 pts) What is the type of the following OCaml expression?

```
(6, [1;2;3;4;5;6])
```

b) (4 pts) What is the type of `foo` in the following OCaml definition?

```
let rec foo x y =  
  match x with  
  [] -> []  
  | h::t -> if h = y then x else y::(foo t y)  
;;
```

c) (4 pts) Write an OCaml expression or definition of type `(int * string) list`

d) (4 pts) Write an OCaml expression or definition of type `(int -> int) -> int -> int`

6. OCaml Execution (15 pts)

To the right of each code snippet, write what the variable `res` will contain after executing the code. Write *FAIL* if an exception is thrown.

a) (3 pts)

```
let f (a,b) = a;;  
let res = f (1,2);;
```

b) (4 pts)

```
let rec map f l = match l with [] -> [] | h::t -> (f h)::map f t  
let clip x =  
  if x < 10 then 10 else  
  if x > 20 then 20 else x  
;;  
let cliplist l = map clip l;;  
let res = cliplist [12;0;17;80];;
```

c) (4 pts)

```
let g x y = fun b -> if x = b then b+x else b+y;;  
let res = g 48 100 2;;
```

d) (4 pts)

```
let rec trans f w =  
  match w with  
  ([x],[y],[z]) -> (f x, f y, f z);;  
trans (fun x -> x+1) ([1],[2],[3;4]);;
```


7. OCaml programming (15 pts)

Below is some code provided in project 2b: the type `int_tree` of a binary search tree of integers, and the function `int_insert` that returns a new tree with an element added.

```
type int_tree =
  IntLeaf
  | IntNode of int * int_tree * int_tree

let rec int_insert x t =
  match t with
  | IntLeaf -> IntNode(x,IntLeaf,IntLeaf)
  | IntNode (y,l,r) when x > y -> IntNode (y,l,int_insert x r)
  | IntNode (y,l,r) when x = y -> t
  | IntNode (y,l,r) -> IntNode(y,int_insert x l,r)
```

On the next page, **Implement any *three* of the following four functions**. (If you do all four, all will be graded, and the result scaled to be out of 15 points.)

1) `print_preorder t`, with type `int_tree -> unit`, prints out the contents of the tree `t` in preorder (i.e., the node, then the left tree's contents, then the right tree's contents). You can use the `print_int` function for printing integers.

2) `min_node t`, with type `int_tree -> int`, returns the minimum element of the tree, or throws exception `Invalid_argument "min_node"` if the tree is empty. Should run in time $O(\text{height of the tree})$.

3) `is_emptytree t`, with type `int_tree -> bool`, returns true if the tree is empty, and false otherwise.

4) `sum t`, with type `int_tree -> int`, returns the sum of all the elements that appear in `t`.

Here are some example uses:

```
let tr = int_insert 7 (int_insert 2 (int_insert 5 IntLeaf));;
print_preorder tr;;          (* prints 527 *)
let x = min_node tr;;        (* x contains 2 *)
let y = is_emptytree tr;;    (* y contains false *)
let w = is_emptytree IntLeaf; (* w contains true *)
let z = sum tr;;             (* z contains 14 *)
```

Answer to problem 7 here