

CMSC 714
Lecture 10
Cray XT4 and IBM Blue Gene/L

Alan Sussman

Notes

- OpenMP project due next Monday
 - Questions?
- Sample topics for group project posted next week

Cray XT4 vs. XT3

- Dual core AMD Opteron nodes (later upgraded to quad core) with integrated memory controller for DDR2 RAM (up to 12.8 GB/sec)
- Nodes connected via SeaStar2 3D toroidal network
 - sustained bi-directional bandwidth of 6GB/sec over 6 links
 - Opteron memory bus directly connected to SeaStar chip (like Intel QPI), not to I/O bus
- Compute nodes run a stripped down version of Linux from Sandia, for scaling
 - to limit effects of OS activities on computations
 - and limit effects of contention between multiple processes/threads running on multiple cores within a node
 - two modes – virtual node (VN) and single/serial node (SN)
- Lustre parallel filesystem
 - multiple I/O nodes on SeaStar network, running full Linux, called object store servers (OSSs), which connect to object store targets (OSTs) that directly talk to I/O devices (disks, RAIDs, etc.)
 - files can be striped across multiple OSTs
 - Paper gets OSS and OST backwards

Cray XT4 evaluation

- **Micro-benchmarks**

- HPCC benchmarks to measure network, node-local and global performance
- network – latency and bandwidth, with different patterns
- node local – different measures for combinations of spatial and temporal locality
- global – SP mode uses 1 processor per node, EP mode for all processors doing same computation, and global model for partitioned computation/data

- **Application benchmarks**

- Community Atmospheric Model – climate/weather modeling
- Parallel Ocean Program – ocean circulation model
- Nanoscale Molecular Dynamics – biomolecule simulations
- Turbulent combustion – coupled fluid dynamics, chemistry, molecular transport (direct numerical simulation)
- Fusion plasma heating – all orders spectral algorithms

Blue Gene/L

- Scalable high performance distributed memory machine, with interesting design decisions
 - main goal is high performance with low power consumption, and high reliability
 - idea is to scale to large configurations of low power, less powerful individual components
 - Distributed memory system, with up to 64K nodes
- Each node is a dual processor chip, with integrated memory controller, network interface, caches, etc.
 - System on chip (SoC) design
 - 2 PowerPC cores, split L1 cache per core, L2 cache/prefetch buffer per core, 1 shared L3 cache, 512MB shared memory
 - L1 caches not hardware coherent, so need software help, other cache levels are coherent
 - Floating point multiply-add instructions for improved power/performance (when used)
 - Plus link chip for network component, for all routing and other network ops between nodes

Blue Gene/L

- 5 distinct networks, all interfaced to node through link chip
 - 3D torus is main message passing network – each node has 6 bi-directional nearest-neighbor links, with cut-through routing
 - Collective network for broadcasts, reductions, etc. – each node has 3 links (parent, 2 children, in a binary tree)
 - also forwards I/O requests to I/O nodes
 - Barrier network – for global sync operations (or other OR or AND operations from a set of nodes)
 - Gigabit Ethernet for file system access (I/O nodes only)
 - Fast Ethernet (100Mb) for initialization, diagnostics, debugging
- Programming model allows for either using each core for a separate process, or use 1 core as a communication co-processor