CMSC 330: Organization of Programming Languages

Smart Pointers in Rust

CMSC330 Spring 2019

Smart Pointers

- A smart pointer is a reference plus metadata, to provide additional capabilities
  - Originated in C++
  - Examples seen so far: `String`, `Vec<T>`
- Usually implemented as `structs`
  - Which must implement the `Deref` and `Drop` traits
- New ones we will see: `Box<T>`, `Rc<T>`
  - There are several others, such as `Ref<T>`
  - And you can make your own; see the book!

Box<T> Smart Pointers

- **`Box<T>`** values point to heap-allocated data
  - The **`Box<T>`** value (the pointer) is on the stack, while its pointed-to **`T`** value is allocated on the heap
  - Has **`Deref`** trait – can be treated like a reference
    - More later
  - Has **`Drop`** trait – will drop its data when it dies

- Uses?
  - Reduce copying (via an ownership move)
  - Create dynamically sized objects
    - Particularly useful for recursive types

Quiz 1

A Box<T> value points to heap-allocated data. Therefore, it cannot be dropped when the owner goes out of scope.

A. True
B. False

Quiz 1

A Box<T> value points to heap-allocated data. Therefore, it cannot be dropped when the owner goes out of scope.

A. True
B. False

Example: Linked List

- Naïve attempt doesn't work
  - Compiler complains that it can't know the size of **`List`**
  - The **`Cons`** case is "inlined" into the **`enum`**
    - Since a **`List`** is recursive, it could be basically any size

```
enum List {
  Nil,
  Cons(i32,List)
}
```

- Use a **`Box`** to add an indirection
  - Now the size is fixed
    - **`i32`** + size of pointer
      - **`Nil`** tag smaller

```
enum List {
  Nil,
  Cons(i32,Box<List>)
}
```

Creating a LinkedList

```
enum List {
  Nil,
  Cons(i32,Box<List>)
}

use List::{Cons, Nil};

fn main() {
  let list = Cons(1,
    Box::new(Cons(2,
      Box::new(Nil))));
  … // data dropped at end of scope
}
```

Deref Trait

- If `x` is an `int` then `&x` is a `&{int}`
  - Can use `*` operator to dereference it, extracting the underlying value
    - `*(&x) == x`
- Can use `*` on `Box<T>` types
  - `Deref` trait requires `deref(&self) -> &T` method
  - So that `*x` translates to `*(x.deref())`

- `deref` returns type `&T` and not `T` so as not to relinquish ownership from inside the `Box` type

Deref Coercion

- The Rust compiler automatically inserts one or more calls to `x.deref()` to get the right type
  - When `&T` required but value `x : U` provided, where `U` implements `Deref` trait
  - In particular, at function and method calls

- Also a `DerefMut` trait
  - Deref coercion works with this too (see Rust book)

Example

```
fn hello(x:&str) {
    println!("hello {}",x);
}
fn main() {
    let m = Box::new(String::from("Rust"));
    hello(&m); //same as hello(&(*m)[..]);
}
```

- `&m` should have type `&str` to pass it to `hello`
- So, compiler calls `m.deref()` to get `&String`, and then `deref()` again to get `&str`

Drop Trait

- Provides the method **`fn drop(&mut self)`**
  - Called when the value implementing the trait dies
  - Should be used to free the underlying resources, e.g., heap memory

- May not call drop method manually
  - Would lead to a **double free** when Rust calls the method again at the end of a scope
  - Can call **`std::mem::drop`** function in some circumstances

Multiple Pointers to a Value

- What's wrong with this code?

```
fn main() {
  let a = Cons(5,
    Box::new(Cons(10,
      Box::new(Nil))));
  let b = Cons(3, Box::new(a));
  let c = Cons(4, Box::new(a));//fails
}
```

  - **`Box::new`** takes ownership of its argument, so the second **`Box::new(a)`** call fails since **`a`** not owned

- How to allow something like this code?

Rc<T> to the Rescue

- Smart Pointer that associates a counter with the underlying reference
- Calling **clone** copies the pointer, not the pointed-to data, and bumps the counter by one
  - By convention, call **`Rc::clone(&a)`** rather than **`a.clone()`**, as a visual marker for future performance debugging
    - In general, calls to **`x.clone()`** are possible issues
- Calling **drop** reduces the counter by one
- When the counter hits zero, the data is **freed**

Rc::clone “Shares” Ownership

```
enum List {
  Nil,
  Cons(i32,Rc<List>)
}

use List::{Cons, Nil};

fn main() {
  let a = Rc::new(Cons(5,
    Rc::new(Cons(10,
      Rc::new(Nil)))));
  let b = Cons(3, Rc::clone(&a));
  let c = Cons(4, Rc::clone(&a));//ok
}
```

Nb. `Rc::strong_count` returns the current ref count

Quiz 2

Rc::clone produces a new pointer to the same value in the heap. Because it shares the reference, programmer has to destroy the pointed-to value.

A. True
B. False

Quiz 2

Rc::clone produces a new pointer to the same value in the heap. Because it shares the reference, programmer has to destroy the pointed-to value.

A. True
B. False

More

- See the Rust book for
  - How to get more flexible borrowing rules using **`Ref<T>`** and **`RefCell<T>`** types
    - Allows for mutability
  - How to use such pointers to make useful tree-based datastructures
    - With lifetimes that may extend beyond the creating scope
  - How you can end up with reference cycles leading to a memory leak
    - And how you can use **`Weak<T>`** types to prevent them
- Check out *The Rustonomicon* for how to implement your own smart pointers!
  - https://doc.rust-lang.org/stable/nomicon/