Scalable Application Layer Multicast

Suman Banerjee
Bobby Bhattacharjee
Christopher Kommareddy

http://www.cs.umd.edu/projects/nice

Group Communication



Network-layer Multicast

Replication at routers



Sequence of Direct Unicasts

Replication only at source

UNIVERSITY OF MARYLAND
TERRAPINS

Application-layer Multicast



Replication at end-hosts

Examples:

- Narada, Yoid, Gossamer, HMTP, Scribe, Bayeux, CAN-multicast, DT, …
- **NICE**

Application-layer Multicast



Replication at end-hosts

Metrics

Tree Quality

State / Control Overheads

Robustness

Talk Outline

- Introduction
- NICE Application-layer Multicast Protocol
- Results
- Conclusions

NICE Application-layer Multicast

- Scales to large group sizes
  - Low average and worst case control overheads
  - Does not compromise tree quality or robustness
- Even low-bandwidth applications are efficient
  - Web tickers

Uses a hierarchy

NICE Topologies

- Control topology
  - Detects host failures and re-structure the overlay
- Data delivery topology
  - Basic path: Implicitly defined by the hierarchy
  - Can be independent of the control path

NICE Hierarchy



A Set of Members

UNIVERSITY OF MARYLAND
TERRAPINS

NICE Hierarchy

Clusters

- Non-overlapping
- Proximity-based
- Size: k to 3k-1



UNIVERSITY OF MARYLAND
TERRAPINS

NICE Hierarchy

Clusters

- Non-overlapping
- Proximity-based
- Size: k to 3k-1



Layer 0







Graph-theoretic center is the cluster leader

UNIVERSITY OF MARYLAND
TERRAPINS

NICE Hierarchy



Leaders form the higher layer and repeats

UNIVERSITY OF MARYLAND
TERRAPINS

NICE Hierarchy



Layer 2

log N layers

UNIVERSITY OF MARYLAND
TERRAPINS

Control Topology

- Soft state about all cluster peers
- HeartBeats



UNIVERSITY OF MARYLAND
TERRAPINS

Control Topology

- Soft state about all cluster peers
- HeartBeats



State and Control message overheads:

Average: Constant Worst case: O(k log N)

UNIVERSITY OF MARYLAND TERRAPINS

Basic Data Path



UNIVERSITY OF MARYLAND
TERRAPINS

Basic Data Path



UNIVERSITY OF MARYLAND
TERRAPINS

Basic Data Path



UNIVERSITY OF MARYLAND
TERRAPINS

Basic Data Path



UNIVERSITY OF MARYLAND
TERRAPINS

NICE Invariants

- Cluster sizes between k and 3k-1
- Cluster leader is the central member
  - Leaders for next higher layer

NICE protocol maintains these invariants

NICE Protocol Operations

- Member Join
- Member Depart
- Cluster Split
- Cluster Merge
- Cluster Refine

Join Procedure



Assume a Rendezvous Point

Join Procedure



UNIVERSITY OF MARYLAND
TERRAPINS

Join Procedure



UNIVERSITY OF MARYLAND
TERRAPINS

Join Procedure



UNIVERSITY OF MARYLAND
TERRAPINS

Join Procedure



UNIVERSITY OF MARYLAND
TERRAPINS

Join Procedure



UNIVERSITY OF MARYLAND
TERRAPINS

Join Procedure



UNIVERSITY OF MARYLAND
TERRAPINS

Join Procedure



Overhead: O(log N) RTTs and O(k log N) messages

- Optimizations possible

Cluster Split

Cluster size: 4 to 11



UNIVERSITY OF MARYLAND
TERRAPINS

Cluster Split



UNIVERSITY OF MARYLAND
TERRAPINS

Cluster Split



UNIVERSITY OF MARYLAND
TERRAPINS

Cluster Split

- Split into two new clusters
- Each new cluster has at least 3k/2 members



UNIVERSITY OF MARYLAND
TERRAPINS

Cluster Split



UNIVERSITY OF MARYLAND
TERRAPINS

Cluster Split



UNIVERSITY OF MARYLAND
TERRAPINS

Cluster Split



UNIVERSITY OF MARYLAND
TERRAPINS

Results

- Simulations
  - 10,000 node Transit-Stub graphs
  - Group sizes upto 2048
  - Comparisons with Narada [CMU]
- Wide-area Experiments
  - Members at 8 sites
  - Group sizes upto 96
- Dynamic joins and (ungraceful) leaves
- Constant rate data source

Evaluation Metrics

- Tree Quality: Stress
  - Number of copies of the same data packet on a link/router
  - Example: Stress on link [A-1] = 2

Application-layer Multicast



- Tree Quality: Stretch
  - Ratio of the overlay latency to the direct unicast latency
  - Example: Stretch for receiver D = 5/3

- State at end-hosts
  - Control overheads

- Robustness
  - Host failures

UNIVERSITY OF MARYLAND TERRAPINS

Example Scenario



UNIVERSITY OF MARYLAND
TERRAPINS

Tree Quality: Stress

First 200 seconds …

Resource usage at links



Tree Quality: Stretch

First 200 seconds …

End-to-end latency to receivers



Failure Recovery

After 1000 secs



UNIVERSITY OF MARYLAND
TERRAPINS

Control Overheads



UNIVERSITY OF MARYLAND
TERRAPINS

Control Overheads

Group Size	Narada-30	NICE
32	**9.23**	**1.03**
128	**65.62**	**1.19**
512	**199.96**	**1.93**
1024	**-**	**2.81**
1560	**-**	**3.28**
2048	**-**	**5.18**

Bandwidth overheads averaged over all network routers

Wide-area Testbed



A: cs.ucsb.edu
B: asu.edu
C: cs.umd.edu
D: glue.umd.edu
E: wam.umd.edu
F: umbc.edu
G: poly.edu
H: ecs.umass.edu

UNIVERSITY OF MARYLAND
TERRAPINS

Failure Recovery

Includes the effects of network losses



Failure Recovery

Includes the effects of network losses



Related Work

- Mesh-first
  - Narada, Gossamer
- Tree-first
  - Yoid, HMTP
- Implicit
  - Scribe, Bayeux, CAN-multicast, Delaunay-Triangulation

"A Comparative Study of Application Layer Multicast Protocols",
S. Banerjee and B. Bhattacharjee
- Available at: http://www.cs.umd.edu/~suman/publications.html

Current Work

- Detailed analysis of tree quality
  - Stress and stretch
- Implementing applications
  - Video delivery

Conclusions

- NICE scales to large member groups
  - Low control overhead
  - Does not sacrifice tree quality or robustness

- Scalability using hierarchy

http://www.cs.umd.edu/projects/nice