

# CMSC330 Spring 2018 Midterm 1

## 9:30am/ 11:00am/ 3:30pm

Name (PRINT YOUR NAME as it appears on gradescope ):

---

Discussion Time (circle one)                      10am   11am   12pm   1pm   2pm   3pm

### Instructions

- Do not start this test until you are told to do so!
- You have 75 minutes to take this midterm.
- This exam has a total of 100 points, so allocate 45 seconds for each point.
- This is a closed book exam. No notes or other aids are allowed.
- Answer essay questions concisely in 2-3 sentences. Longer answers are not needed.
- For partial credit, show all of your work and clearly indicate your answers.
- Write neatly. Credit cannot be given for illegible answers.

	Problem	Score
1	Programming Language Concepts	/10
2	Ruby Regular Expressions	/10
3	Ruby execution	/13
4	Ruby Programming	/18
5	OCaml Typing	/17
6	OCaml Execution	/15
7	OCaml Programming	/17
	Total	/100

# 1. [10 pts] Programming Language Concepts

1.1 [7 pts] Circle the correct answer:

- a. *True / False*: [1,2,3] is a list/array of three ints in both OCaml and Ruby
- b. *True / False*: Static type checking occurs at compile time
- c. *True / False*: In dynamically typed languages, a type error will go unnoticed if the line containing the error is never executed
- d. The OCaml compiler does which of the following if you omit a case in a pattern match:        *Nothing / Emits a warning / Emits an error*
- e. *True / False*: Ruby variables are declared explicitly
- f. *True / False*: All values in Ruby are objects
- g. *True / False*: Ruby code blocks are *first class*, e.g., they can be stored in arrays

1.2 [3 pts] Show the contents of the closure for f after executing the following code:

```
let add = (fun x -> (fun y -> x + y + 10));;  
let f = add 5;;
```

Code	Environment

## 2. [10 pts] Ruby Regular Expressions

2.1. [3 pts] Write a regular expression that accepts precisely 8, 9, or 10 letters

2.2. [3 pts] Write a string that matches the following regular expression:

```
/^www(\.[a-zA-Z]+)*(\.[a-zA-Z]{2,3})$/
```

2.3. [4 pts] Circle all of the given strings that match the following regular expression

```
/^[0-9]+(,[0-9])*/
```

"3562"

"0432,7,7384"

"8392,6,3"

"8265,"

### 3. [13 pts] Ruby execution

Write the output of the following Ruby code. If there is an error, then write **ERROR**. If nil is printed write "nil" and not the empty string. *Hint*: select invokes the block passing in successive elements, returning an array containing those elements for which the block returns a true value.

3.1. [2 pts]

```
x = []  
x[3] = 4  
puts x["3"]
```

Output:

3.2. [2 pts]

```
m = {"hello" => 3, "world" => 4}  
puts m[3]  
puts m["hello"]
```

Output:

3.3. [2 pts]

```
x = {}  
x["hi"].push(3)  
puts x["hi"]
```

Output:

3.4. [2 pts]

```
x = [2, false, 4, nil, 6, 0, 8]  
puts x.select {|y| y}
```

Output:

3.5. **[2 pts]**

```
x = "hello"  
y = "hello"  
puts (x == y)  
puts (x.equal? y)
```

**Output:**

3.6. **[3 pts]**

```
class Foo  
  @@x = []  
  def initialize(ele)  
    @@x.push ele  
  end  
  
  def add(ele)  
    @@x.push ele  
    @@x  
  end  
end  
  
f = Foo.new 5  
g = Foo.new "hi"  
puts (f.add true)
```

**Output:**

## 4. [18 pts] Ruby Programming

Implement a `Graph` class, which represents a *directed graph* as a collection of nodes that are linked by edges. *Cycles, including self-edges, are allowed*, but there can be *at most one edge between any pair of nodes*. A template for your implementation is given on the next page. You may **NOT** edit the `initialize` method, whose implementation implies you should store your graph as a hash. Implement the following methods.

4.1 [8 pts] `addEdge(str)` adds an edge represented by the `str` input parameter to the graph. The `str` input parameter has the format 'start: nodename end: nodename', where a valid nodename is a combination of one or more letters (uppercase or lowercase) followed by a dash ('-') followed by one or more digits. For example:

```
g = Graph.new
g.addEdge("start: Node-5 end: tidepod-6")
g.addEdge("start: tidepod-6 end: A-7")
g.addEdge("start: A-8 end: tidepod-6")
```

will create a graph `g` with the edges (Node-5, tidepod-6), (tidepod-6, A-7), and (A-8, tidepod-6) in it. If the input string to `addEdge` is incorrectly formatted, then nothing will be added. For example:

```
g.addEdge("start: Node5 end: hello-6")
```

will add no edges to `g` because `Node5` is an invalid nodename.

4.2 [5 pts] `inDegree(node)` takes a node (a string) and returns the number of edges ending at that node. For example, for the graph `g` above, `g.inDegree("Node-5")` is 0, while `g.inDegree("tidepod-6")` is 2. The `inDegree` of a node with no incoming edges (or any edges at all) in the graph is 0.

4.3 [5 pts] `outDegree(node)` takes a node (a string) and returns the number of edges that start at that node. For example, for graph `g` above, `g.outDegree("Node-5")` and `g.outDegree("A-8")` are both 1. A node with no outgoing edges has degree zero, as does a node with no edges at all.

Implement your solutions on the next page.

```
class Graph
  def initialize      # do not change, add to, or delete this method
    @g = { }
  end

  def addEdge(str)

  end

  def inDegree(node)

  end

  def outDegree(node)

  end
end
end
```

## 5. [17 pts] OCaml Typing

Determine the type of the following definitions. Write **ERROR** if there is a type error.

### 5.1. [2 pts]

```
type 'a option = Some of 'a | None
let f a =
  if a < 0 then None else Some a
;;
```

### 5.2. [3 pts]

```
let f x y = [x;y]
;;
```

### 5.3. [3 pts]

```
let rec g l =
  match l with
  | [] -> []
  | [x] -> []
  | h1::h2::t -> (h1,h2)::(g t)
;;
```

Write an expression that has the following type, **without using type annotations**

5.4 **[3 pts]** `bool -> bool -> bool list`

5.5 **[3 pts]** `(int * 'a) -> int`

5.6 **[3 pts]**

```
let rec fold f a l =  
  match l with  
  | [] -> a  
  | h::t -> fold f (f a h) t  
  
fold: ('a -> 'b -> 'a) -> 'a -> 'b list -> 'a
```

Define a function `f` that when used in the following expression will not produce any type errors. The implementation and type of `fold` are given for reference, above.

```
fold f ([],0) [5;4;3;2;1]
```

## 6. [15 pts] OCaml Execution

```
let rec fold f a l =
  match l with
  | [] -> a
  | h::t -> fold f (f a h) t

let rec map f l =
  match l with
  | [] -> []
  | h::t -> (f h)::(map f t)
```

Determine the final value of the following expressions. Write **EXCEPTION** if an exception is thrown or **ERROR** if there is a type error.

6.1. [2 pts] `let f a =`  
    `if a = 1 then "harambe"`  
    `else 0 in`  
    `f 5`

6.2. [3 pts] (you might find it useful to refer to the `map` and `fold` definitions given above)

```
let xs = map (fun (x,y) -> x) [(2,"a");(3,"b")] in
fold (fun a h -> a * h) 1 xs
```

6.3. [2 pts] `let f a = fun b -> if a > b then a else b in`  
    `map (f 1) [0;1;2;3]`

6.4. **[2 pts]** `let f a b = if a=b then (a-1) else (b+1) in  
f (4,8)`

6.5. **[3 pts]** `let y = 4 in  
let sub x y = x - y in  
let part = sub 3 in  
let y = 2 in  
(sub 3 7, part y)`

6.6. **[3 pts]** (you might find it useful to refer to the type 'a option given in 5.1)

```
let rec f l =  
  match l with  
  | [] -> 0  
  | None::t -> f t  
  | (Some _)::t -> 1 + (f t)  
in f [Some "a"; None; None; Some "b"; Some "c"]
```

## 7. [17 pts] OCaml Programming

7.1. [8 pts] Write a function `int_of_digits` that takes a list of digits and returns an `int` having those digits. **For full credit, you must implement `int_of_digits` using `fold`** (see the top of question 6 for its definition). Examples:

```
int_of_digits [] = 0
int_of_digits [0] = 0
int_of_digits [1;2;3] = 123
int_of_digits [1;0] = 10
```

Answer:

```
let int_of_digits lst =
```

**7.2. [9 points]** Using the `int_tree` type below, write a function `sum_level` that sums all the node values at a given level within the tree (starting at 0 for the top). Leaves present at a given level do not contribute (i.e., they have count zero). If the level is greater than the depth of the tree, return 0.

```
type int_tree =  
  IntLeaf  
| IntNode of int * int_tree * int_tree  
;;
```

Examples:

```
sum_level (IntLeaf) 0 = 0;;  
sum_level (IntLeaf) 1 = 0;;  
sum_level (IntNode (1,IntNode(2,IntLeaf,IntLeaf),IntLeaf)) 0 = 1;;  
sum_level (IntNode (1,IntNode(2,IntLeaf,IntLeaf),IntLeaf)) 1 = 2;;  
sum_level (IntNode (1,IntNode(2,IntLeaf,IntLeaf),IntNode(3,IntLeaf,IntLeaf))) 1 = 5;;
```

Write your code here (add the `rec` keyword if you need it):

```
let sum_level t n =
```

