

An Applicable Family of Data Flow Testing Criteria

- Assumptions about the program
 - No
 - goto statements
 - with
 - variant records
 - Functions having 'var' parameters
 - By reference
 - Procedural or functional parameters
 - Conformant arrays
 - size of an array parameter is not known to the called function until run-time
 - Every Boolean expression that determines the flow of control has at least one occurrence of a variable or a call to the function 'eof' or 'eoln'

Program Structure

- Program consists of 'blocks'
- Block
 - Sequence of statements
 - Whenever the first statement is executed, the remaining statements in the block are executed in the given order
- Can be represented by a flow graph

Classifying each variable occurrence

- **Definition**
 - Value is stored in a memory location
- **Use**
 - Value is fetched from a memory location
- **Undefinition**
 - Value and location becomes unbound
- **C-use**
 - Use in a computation or output statement
 - Associated with each node
- **P-use**
 - Use in a predicate
 - Associated with each edge

Simple Statements

Assignment statement: $v := \text{expr};$

Node i has c-uses of each variable in expr followed by a definition of v .



Simple Statements

Input/Output statements:

```
read(v1,...,vn);
readln(v1,...,vn);
read(f,v1,...,vn);
readln(f,v1,...,vn);
```

Node i has definitions of v1,...,vn.
If the file variable f is present then node i
also has a c-use followed by a definition of f.

```
write(e1,...,en);
writeln(e1,...,en);
write(f,e1,...,en);
writeln(f,e1,...,en);
```

Node i has c-uses of each variable occurring in e1,...,en..
If the file variable f is present then node i
also has a definition followed by a c-use of f.



Simple Statements

Procedure call: P(e1,...,en);

Node j has c-uses of each variable occurring in
the expressions e1,...,en.
These are followed by definitions of each actual
parameter which corresponds to a var formal parameter.


Nodes i and k are included to assure that
the procedure call has its own node.



Repetitive Statements

while statement: while B do S;

Let h be the entry node to subgraph S .
Edges (i,h) and (i,j) have p-uses of each variable in the boolean expression B .




Repetitive Statements

for statement:

for $v := e1$ to $e2$ do S ;
for $v := e1$ downto $e2$ do S ;

Let tmp be a new variable.
Let f and g be the entry and exit nodes, respectively, of S . Node h has c-uses of each variable in $e1$, followed by a definition of v and c-uses of each variable in $e2$ followed by a definition of tmp . Edges (i,f) and (i,j) have p-uses of v and tmp . Node g has a c-use followed by a def of v .




Repetitive Statements

repeat statement:

repeat $S_1; \dots; S_n$ until B ;

Let j be the entry node of S_1 , and let k be the exit node of S_n .

Edges (k,j) and (k,i) have p-uses of each variable in the boolean expression B .



Conditional Statements

if-then-else statement


if B then S_1 ;

if B then S_1 else S_2 ;

Let k and j be the entry nodes of S_1 and S_2 , respectively.

Edges (i,j) and (i,k) have p-uses of each variable in the boolean expression B .


if there is no "else" part then subgraph S_2 has a single node corresponding to an empty block.



Conditional Statements

```
case e1 of
  label-list1 : S1;
  ...
  label-listn : Sn
end;
```

Let j_1, \dots, j_n be the entry nodes of S_1, \dots, S_n , respectively.
Edges $(i, j_1), \dots, (i, j_n)$ have p-uses of each variable in the expression e_1 .



Entry and exit nodes

- **Entry node**
 - Has the definition of
 - Each parameter
 - Each non-local variable that is used in the program
 - Input buffer input \uparrow
- **Exit node has**
 - An undefinition of each local variable
 - A c-use of each variable parameter
 - A c-use of each non-local variable
 - A c-use of the input buffer input \uparrow

Arrays

- It is impossible to determine the particular array element which is being used or defined in an occurrence of an array variable
 - $A[2]$
 - $A[i+j]$
- Definition of $a[expr]$
 - A c-use of each variable in $expr$
 - Followed by a definition of a
- Use of $a[expr]$
 - c-uses of all the variables in $expr$
 - Followed by a use of a

Pointers

- Impossible to determine statically the memory location to which a pointer points
- Syntactic treatment
- If p is a pointer variable
 - Definition of p^{\wedge}
 - C-use of p
 - Followed by a definition of p^{\wedge}
 - Use of p^{\wedge}
 - C-use of p
 - Followed by a c-use of p^{\wedge}
- Ignore definitions and uses of p^{\wedge}

Records & Files

- Records
 - Each field is treated as an individual variable
 - Any unqualified occurrence of a record is treated as an occurrence of each field
- File variables
 - Considering the effect on the file buffer

Simplifying Assumptions

- No interprocedural dataflow analysis
- Ignore pointers
- Array reference simplification
- No aliasing/side-effects
- Consequences
 - Perhaps “less than perfect” test data

Global Definition

- **Global c-use**
 - A c-use of x in node i is global if x has been assigned in some block other than i
- **Def-clear path wrt x "from node i to node j " and "from node i to edge (n_m, j) "**
 - A path $(i, n_1, n_2, \dots, n_m, j)$ containing no definitions or undefinitions of x in nodes n_1, n_2, \dots, n_m
- **Global definition of x**
 - **A node i has a global definition of a variable x if**
 - it has a definition of x and
 - there is a def-clear path wrt x from node i to some node containing
 - a global c-use or
 - edge containing a p-use of x

Restricted Programs Class

- **Satisfying the following properties**
 - **NSUP**
 - No-syntactic-undefined-p-use Property
 - For every p-use of a variable x on an edge (i, j) , in P , there is some path from the start node to edge (i, j) , which contains a global definition of x
 - **NSL**
 - Non-straight-line property
 - P has at least one conditional or repetitive statement
 - » At least one node in P 's flow-graph has more than one successor
 - » At least one variable has a p-use in P

Def-use graph

- Obtained from the flow graph
- Associate with each node the sets
 - **C-use(i)**
 - Variables which have global c-uses in block-i
 - **Def(I)**
 - Variables which have global definitions in block-i
- Associate with each edge (i,j)
 - **P-use(i,j)**
 - Variables which have p-uses on edge (i,j)
- Define sets of nodes
 - **dcu(x,i)**
 - Nodes j such that $x \in \text{c-use}(j)$ and there is a def-clear paths with respect to x from i to j
 - **dpu(x,i)**
 - Edges (j,k) such that $x \in \text{p-use}(j,k)$ and there is a def-clear path with respect to x from i to (j,k)

Definitions for def-use graph

V = the set of variables
 N = the set of nodes
 E = the set of edges
 $\text{def}(i)$ = $\{x \in V \mid x \text{ has a global definition in block } i\}$
 $\text{c-use}(i)$ = $\{x \in V \mid x \text{ has a global c-use in block } i\}$
 $\text{p-use}(i,j)$ = $\{x \in V \mid x \text{ has a p-use in edge } (i,j) \}$
 $\text{dcu}(x,i)$ = $\{j \in N \mid x \in \text{c-use}(j) \text{ and there is a def-clear path wrt } x \text{ from } i \text{ to } j\}$
 $\text{dpu}(x,i)$ = $\{(j,k) \in E \mid x \in \text{p-use}(j,k) \text{ and there is a def-clear path wrt } x \text{ from } i \text{ to } (j,k) \}$

Explanation

- If $x \in \text{def}(i)$ and $j \in \text{dcu}(x,i)$, then
 - x has a global definition in node i and
 - A c-use in node j , and
 - There is a definition clear path with respect to x from node i to node j
- Hence
 - It may be possible for control to reach node j with the variable x having the value which was assigned to it in node i

More definitions

- Definition-c-use association
 - Triple (i,j,x) where i is a node containing a global definition of x and $j \in \text{dcu}(x,i)$
- Definition-p-use association
 - Triple $(i,(j,k),x)$ where i is a node containing a global definition of x and $(j,k) \in \text{dpu}(x,i)$
- A path $(n_1, n_2, \dots, n_j, n_k)$ is a du-path wrt x if n_1 has a global definition of x and either
 - n_k has a global c-use of x and (n_1, \dots, n_j, n_k) is a def-clear simple path wrt x , and
 - (n_j, n_k) has a p-use of x and (n_1, \dots, n_j) is a def-clear loop-free path wrt x
- An association is a definition-c-use association, a definition-p-use association, or a du-path

Yet more definitions

- **Complete path**
 - Path from the entry node to the exit node
- **Covering**
 - A complete path π covers a definition-c-use association (i,j,x) if it has a definition clear subpath wrt x from i to j
 - A complete path π covers a definition-p-use association $(i,(j,k),x)$ if it has a definition clear subpath wrt x from i to (j,k)
 - π covers a du-path π' if π' is a subpath of π
 - The set Π of paths covers an association if some element of the set does
 - A test set T covers an association if the elements of T cause the execution of the set of paths Π , and Π covers the association

Finally, the criteria

- **Intuitively**
 - The family of DF testing criteria is based on requiring that
 - the test data execute definition-clear paths from each node containing a global definition of a variable to specified nodes containing
 - global c-uses and
 - edges containing p-uses of that variable
 - For each variable definition, the criteria require that
 - All/some definition-clear paths wrt that variable from the node containing the definition to all/some of the uses/c-uses/p-uses reachable by some such paths be executed

All-defs criterion

- If variable x has a global definition in node i , the all-defs criterion requires the test data to exercise some path which goes from i to some node or edge at which the value assigned to x in node i is used

All-uses criterion

- If variable x has a global definition in node i , the all-uses criterion requires the test data to exercise at least one path which goes from i to each node and edge at which the value assigned to x in node i is used

All-DU-paths criterion

- If variable x has a global definition in node i , the all-DU-paths criterion requires the test data to exercise all paths which go from i to each node and edge at which the value assigned to x in node i is used

Other DF testing criteria

- All-p-uses
- All-c-uses
- All-p-uses/some-c-uses
- All-c-uses/some-p-uses


Definitions of DF criteria

CRITERION	ASSOCIATIONS REQUIRED
All-defs	Some (i,j,x) s.t. $j \in \text{dca}(x,i)$ or some $(i,(j,k),x)$ s.t. $(j,k) \in \text{dpu}(x,i)$.
All-c-uses	All (i,j,x) s.t. $j \in \text{dca}(x,i)$.
All-p-uses	All $(i,(j,k),x)$ s.t. $(j,k) \in \text{dpu}(x,i)$.
All-p-uses/some-c-uses	All $(i,(j,k),x)$ s.t. $(j,k) \in \text{dpu}(x,i)$. In addition, if $\text{dpu}(x,i) = \emptyset$ then some (i,j,x) s.t. $j \in \text{dca}(x,i)$. Note that since i has a <i>global</i> definition of x , $\text{dpu}(x,i) = \emptyset \Rightarrow \text{dca}(x,i) \neq \emptyset$.
All-c-uses/some-p-uses	All (i,j,x) s.t. $j \in \text{dca}(x,i)$. In addition, if $\text{dca}(x,i) = \emptyset$ then some $(i,(j,k),x)$ s.t. $(j,k) \in \text{dpu}(x,i)$. Note that since i has a <i>global</i> definition of x , $\text{dca}(x,i) = \emptyset \Rightarrow \text{dpu}(x,i) \neq \emptyset$.
All-uses	All (i,j,x) s.t. $j \in \text{dca}(x,i)$ and all $(i,(j,k),x)$ s.t. $(j,k) \in \text{dpu}(x,i)$.
All-du-paths	All du-paths from i to j with respect to x for each $j \in \text{dca}(x,i)$ and all du-paths from i to (j,k) with respect to x for each $(j,k) \in \text{dpu}(x,i)$.

"includes"

- Criterion C_1 includes criterion C_2 iff
 - For every subprogram, any test set that satisfies C_1 also satisfies C_2
- C_1 strictly includes C_2 , iff
 - denoted $C_1 \Rightarrow C_2$,
 - C_1 includes C_2 and for some subprogram P there is a test set that satisfies C_2 but does not satisfy C_1

Includes relationship



Applicability

- It may be the case that no test set for program P satisfies criterion C
 - Infeasible paths
- Tailor the DF criteria so that they are applicable
- Assumptions
 - All aliases are known
 - All side effects are known
 - No element of the test set causes the program to crash
 - Execution of entry node to exit node

Executable/Feasible Paths

- Recall
 - Complete path
 - Path from the entry node to the exit node
- Executable/feasible complete path
 - A complete path that is executed on some assignment of values to input variables
- Executable/feasible path
 - A subpath of an executable complete path

Recall Definition

- Definition-c-use association
 - Triple (i,j,x) where i is a node containing a global definition of x and $j \in \text{dcu}(x,i)$
- Definition-p-use association
 - Triple $(i,(j,k),x)$ where i is a node containing a global definition of x and $(j,k) \in \text{dpu}(x,i)$
- A path $(n_1, n_2, \dots, n_j, n_k)$ is a du-path wrt x if n_1 has a global definition of x and either
 - n_k has a global c-use of x and (n_1, \dots, n_j, n_k) is a def-clear simple path wrt x , and
 - (n_j, n_k) has a p-use of x and (n_1, \dots, n_j) is a def-clear loop-free path wrt x
- An association is a definition-c-use association, a definition-p-use association, or a du-path

Executable Associations

- Definition
 - An association is executable if there is some executable complete path that covers it; otherwise it is unexecutable
- $\text{fdcu}(x,i) \in \text{dcu}(x,i)$
 - Nodes j such that $x \in \text{c-use}(j)$ and there is an executable definition clear path wrt x from i to j
- $\text{fdpu}(x,i) \in \text{dpu}(x,i)$
 - Edges (j,k) such that $x \in \text{p-use}(j,k)$ and there is an executable definition clear path wrt x from i to (j,k)


Equivalently

- $\text{fdcu}(x,i) =$
 - $\{j \in \text{dcu}(x,i) \mid \text{the association } (i,j,k) \text{ is executable}\}$
- $\text{fdpu}(x,i) =$
 - $\{(j,k) \in \text{dpu}(x,i) \mid \text{the association } (i,(j,k),x) \text{ is executable}\}$
- Intuitively
 - new criterion C^* for each DF criterion C
 - By selecting the required associations from $\text{fdcu}(x,i)$ and $\text{fdpu}(x,i)$ instead of from $\text{dcu}(x,i)$ and $\text{dpu}(x,i)$

Feasible Data-flow Criteria (FDF)


CRITERION	REQUIRED ASSOCIATIONS
(all-defs)*	if $\text{fdcu}(x,i) \cup \text{fdpu}(x,i) \neq \emptyset$ then some (i,j,x) s.t. $j \in \text{fdcu}(x,i)$ or some $(i,(j,k),x)$ s.t. $(j,k) \in \text{fdpu}(x,i)$.
(all-c-uses)*	all (i,j,x) s.t. $j \in \text{fdcu}(x,i)$.
(all-p-uses)*	all $(i,(j,k),x)$ s.t. $(j,k) \in \text{fdpu}(x,i)$.
(all-p-uses/some-c-uses)*	all $(i,(j,k),x)$ s.t. $(j,k) \in \text{fdpu}(x,i)$. In addition, if $\text{fdpu}(x,i) = \emptyset$ and $\text{fdcu}(x,i) \neq \emptyset$ then some (i,j,x) s.t. $j \in \text{fdcu}(x,i)$.
(all-c-uses/some-p-uses)*	all (i,j,x) s.t. $j \in \text{fdcu}(x,i)$. In addition, if $\text{fdcu}(x,i) = \emptyset$ and $\text{fdpu}(x,i) \neq \emptyset$ then some $(i,(j,k),x)$ s.t. $(j,k) \in \text{fdpu}(x,i)$.
(all-uses)*	all (i,j,x) s.t. $j \in \text{fdcu}(x,i)$ and all $(i,(j,k),x)$ s.t. $(j,k) \in \text{fdpu}(x,i)$.
(all-du-paths)*	all executable du-paths with respect to x from i to j s.t. $j \in \text{dcu}(x,i)$ and all executable du-paths with respect to x from i to (j,k) for each $(j,k) \in \text{dpu}(x,i)$.

Includes Relationships




Interprocedural DF Testing

- Most DF testing methodologies deal with dependencies that exist within a procedure (i.e., *intraprocedural*)
- Data dependencies also exist among procedures
- Requires analysis of the flow of data across procedure boundaries
- Calls and Returns
- Direct dependencies (single call/return)
- Indirect dependencies (multiple calls/returns)




The Def-uses



A test case

$S = \{3, 5, 1, 6\}$

$F = 1$
 $L = 4$



Any missed
def-uses?

```
module Main
declare
  S: an array 1..N of integer;
  I,MAX,MIN: integer;
begin
  for I := 1 to N do read(S[I]);
  GetMax(1,N,MAX);
  write(MAX);
end;

procedure GetMax;
input
  F,L: integer;
  MX: reference integer;
declare M1,M2,MD: integer;
begin
  if F+1=L then PairMax(S[F],S[L],MX)
  else begin
    MD := (F+L) DIV 2;
    GetMax(F,MD,M1);
    GetMax(MD+1,L,M2);
    PairMax(M1,M2,MX);
  end;
end;

procedure PairMax;
input L,J,K: reference integer;
begin
  if I>J then K := I
  else K := J;
end;
```