

# Announcements

- Program #1
  - Due Friday
- Reading
  - Continue scheduling

# Types of Scheduling

- At least 4 types:
  - long-term - add to pool of processes to be executed
  - medium-term - add to number of processes partially or fully in main memory
  - short-term - which available process will be executed by the processor
  - I/O - which process's pending I/O request will be handled by an available I/O device
- Scheduling changes the *state* of a process

# Scheduling criteria

- Per processor, or system oriented
  - CPU utilization
    - maximize, to keep as busy as possible
  - throughput
    - maximize, number of processes completed per time unit
- Per process, or user oriented
  - turnaround time
    - minimize, time of submission to time of completion.
  - waiting time
    - minimize, time spent in ready queue - affected solely by scheduling policy
  - response time
    - minimize, time to produce first output
    - most important for interactive OS

# Scheduling criteria non-performance related

- Per process
  - predictability
    - job should run in about the same amount of time, regardless of total system load
- Per processor
  - fairness
    - don't starve any processes, treat them all the same
  - enforce priorities
    - favor higher priority processes
  - balance resources
    - keep all resources busy

# Medium vs. Short Term Scheduling

- **Medium-term scheduling**

- Part of swapping function between main memory and disk
  - based on how many processes the OS wants available at any one time
  - must consider memory management if no virtual memory (VM), so look at memory requirements of swapped out processes

- **Short-term scheduling (dispatcher)**

- Executes most frequently, to decide which process to execute next
- Invoked whenever event occurs that interrupts current process or provides an opportunity to preempt current one in favor of another
- Events: **clock interrupt, I/O interrupt, OS call, signal**

# Long-term scheduling

- Determine which programs admitted to system for processing - controls degree of multiprogramming
- Once admitted, program becomes a process, either:
  - added to queue for short-term scheduler
  - swapped out (to disk), so added to queue for medium-term scheduler
- **Batch Jobs**
  - Can system take a new process?
    - more processes implies less time for each existing one
    - add job(s) when a process terminates, or if percentage of processor idle time is greater than some threshold
  - Which job to turn into a process
    - first-come, first-serve (FCFS), or to manage overall system performance (e.g. based on priority, expected execution time, I/O requirements, etc.)



# Short-term scheduling algorithms

- **First-Come, First-Served (FCFS, or FIFO)**
  - as process becomes ready, join Ready queue, scheduler always selects process that has been in queue longest
  - better for long processes than short ones
  - favors CPU-bound over I/O-bound processes
  - need priorities, on uniprocessor, to make it effective


# Algorithms (cont.)

- Round-Robin (RR)

- use preemption, based on clock - time slicing
  - generate interrupt at periodic intervals
- when interrupt occurs, place running process in Ready queue, select next process to run using FCFS
- what's the length of a time slice
  - short means short processes move through quickly, but high overhead to deal with clock interrupts and scheduling
  - guideline is time slice should be slightly greater than time of “typical job” CPU burst
- problem dealing with CPU and I/O bound processes

# Priority Based Scheduling

- **Priorities**
  - assign each process a priority, and scheduler always chooses process of higher priority over one of lower priority
- **More than one ready queue, ordered by priorities**



# Priority Algorithms

- Fixed Queues

- processes are statically assigned to a queue
- sample queues: system, foreground, background

- Multilevel Feedback

- processes are dynamically assigned to queues
- penalize jobs that have been running longer
- preemptive, with dynamic priority
- have  $N$  ready queues (RQ0-RQ $N$ ),
  - start process in RQ0
  - if quantum expires, moved to  $i + 1$  queue

# Feedback scheduling (cont.)

- problem: turnaround time for longer processes
  - can increase greatly, even starve them, if new short jobs regularly enter system
- solution1: vary preemption times according to queue
  - processes in lower priority queues have longer time slices
- solution2: promote a process to higher priority queue
  - after it spends a certain amount of time waiting for service in its current queue, it moves up
- solution3: allocate fixed share of CPU time to jobs
  - if a process doesn't use its share, give it to other processes
  - variation on this idea: lottery scheduling
    - assign a process “tickets” (# of tickets is share)
    - pick random number and run the process with the winning ticket.

# UNIX System V

- Multilevel feedback, with
  - RR within each priority queue
  - 10ms second preemption
  - priority based on process type and execution history, lower value is higher priority
- priority recomputed once per second, and scheduler selects new process to run
- For process  $j$ ,  $P(i) = \text{Base} + \text{CPU}(i-1)/2 + \text{nice}$ 
  - $P(i)$  is priority of process  $j$  at interval  $i$
  - Base is base priority of process  $j$
  - $\text{CPU}(i) = U(i)/2 + \text{CPU}(i-1)/2$ 
    - $U(i)$  is CPU use of process  $j$  in interval  $i$
    - exponentially weighted average CPU use of process  $j$  through interval  $i$
  - nice is user-controllable adjustment factor

# UNIX (cont.)

- Base priority divides all processes into (non-overlapping) fixed bands of decreasing priority levels
  - swapper, block I/O device control, file manipulation, character I/O device control, user processes
- bands optimize access to block devices (disk), allow OS to respond quickly to system calls
- penalizes CPU-bound processes w.r.t. I/O bound
- targets general-purpose time sharing environment

# Example: Windows NT/XP

- Target:
  - single user, in highly interactive environment
  - a server
- preemptive scheduler with multiple priority levels
- flexible system of priorities, RR within each, plus dynamic variation on basis of current thread activity for *some* levels
- 2 priority bands, real-time and variable, each with 16 levels
  - real-time ones have higher priority, since require immediate attention(e.g. communication, real-time task)

## Windows NT/XP (cont.)

- In real-time class, all threads have fixed priority that never changes
- In variable class, priority begins at an initial value, and can change, up or down
  - FIFO queue at each level, but thread can switch queues
- Dynamic priority for a thread can be from 2 to 15
  - if thread interrupted because time slice is up, priority lowered
  - if interrupted to wait on I/O event, priority raised
  - favors I/O-bound over CPU-bound threads
  - for I/O bound threads, priority raised more for interactive waits (e.g. keyboard, display) than for other I/O (e.g. disk)

# Multi-Processor Scheduling

- Multiple processes need to be scheduled together
  - Called gang-scheduling
  - Allowing communicating processes to interact w/o/ waiting
- Try to schedule processes back to same processor
  - Called affinity scheduling
    - Maintain a small ready queue per processor
    - Go to global queue if nothing local is ready