

ANNOUNCEMENTS

- ❖ No posting of code in the forum
- ❖ Make sure you complete the terpconnect part during the weekend. Some students need help from OIT (if you wait until the last minute you may not get that help).
- ❖ **We update slides/example often. Always get the lecture material from the web site**
- ❖ **Remember to use Chrome for the project**
- ❖ Check class announcements daily

KINDS OF SELECTORS

- ❖ **Type Selectors** → Those based on the name of an HTML tag (e.g., p, table, etc.)
 - ❖ p { color: red; }
- ❖ **Pseudo-classes** → attached to selectors to specify a state. Four popular pseudo-classes are:
 - ❖ a:link → initial color of a link
 - ❖ a:visited → color for a visited link
 - ❖ a:hover → color when mouse hover over link
 - ❖ a:active → color during the clicking of the link
 - ❖ Order is important (LoVeHAte)
- ❖ **Example:** Selectors.html, Selectors.css

KINDS OF SELECTORS

- ❖ **Class Selectors** → Allow us to apply the same rules to many elements
 - ❖ Use when you need to apply a style many times in your document
 - ❖ Created with a period (also known as full stop)
 - ❖ **Example:** Selectors.html, Selectors.css
- ❖ **ID Selectors** → Similar to class selectors but appear only once in the document
 - ❖ Used when you need to apply a style only once in your document
 - ❖ Created using #
 - ❖ **Example:** Selectors.html, Selectors.css
- ❖ **Others**
 - ❖ Descendant, child, attribute, universal selectors

IN-CLASS LAB (LAST 20 MINUTES)
