

CMSC 330: Organization of Programming Languages

Ruby Regular Expressions

String Processing in Ruby

- ▶ Earlier, we motivated scripting languages using a popular application of them: string processing
- ▶ The Ruby **String** class provides many useful methods for manipulating strings
 - Concatenating them, grabbing substrings, searching in them, etc.
- ▶ A key feature in Ruby is its native support for **regular expressions**
 - Very useful for parsing and searching
 - First gained popularity in Perl

String Operations in Ruby

- `"hello".index("l", 0)`
 - Return index of the first occurrence of string in `s`, starting at `n`
- `"hello".sub("h", "j")`
 - Replace first occurrence of `"h"` by `"j"` in string
 - Use `gsub` ("global" sub) to replace all occurrences

► Consider these three examples again

- All involve **searching** in a string for a certain pattern
- What if we want to find more complicated patterns?
 - Find Steve, Stephen, Steven, Stefan, Esteve

Regular Expressions

- ▶ A way of describing patterns or sets of strings
 - Searching and matching
 - Formally describing strings
 - The symbols (lexemes or tokens) that make up a language
- ▶ Common to lots of languages and tools
 - awk, sed, perl, grep, Java, OCaml, C libraries, etc.
 - Popularized (and made fast) as a language feature in Perl
- ▶ Based on some really elegant theory
 - Future lecture

Example Regular Expressions in Ruby

- ▶ `/Ruby/`
 - Matches exactly the string "Ruby"
 - Regular expressions can be delimited by `/`'s
 - Use `\` to escape `/`'s in regular expressions
- ▶ `/(Ruby|OCaml|Java)/`
 - Matches either "Ruby", "OCaml", or "Java"
- ▶ `/(Ruby|Regular)/` or `/R(uby|egular)/`
 - Matches either "Ruby" or "Regular"
 - Use `()`'s for grouping; use `\` to escape `()`'s

Using Regular Expressions

- ▶ Regular expressions are instances of **Regexp**
 - We'll see use of a **Regexp.new** later
- ▶ Basic matching using **=~** method of **String**

```
line = gets           # read line from standard input
if line =~ /Ruby/ then # returns nil if not found
  puts "Found Ruby"
end
```

- ▶ Can use regular expressions in **index**, **search**, etc.

```
offset = line.index(/(MAX|MIN)/) # search starting from 0
line.sub(/(Perl|Python)/, "Ruby") # replace
line.split(/(\t|\n| )/)           # split at tab, space,
                                   # newline
```

Repetition in Regular Expressions

- ▶ `/(Ruby)*/`
 - `{ "", "Ruby", "RubyRuby", "RubyRubyRuby", ... }`
 - `*` means *zero or more occurrences*
- ▶ `/Ruby+/`
 - `{ "Ruby", "Rubyy", "Rubyyy", ... }`
 - `+` means *one or more occurrence*
 - so `/e+/` is the same as `/ee*/`
- ▶ `/(Ruby)?/`
 - `{ "", "Ruby" }`
 - `?` means *optional*, i.e., zero or one occurrence

Repetition in Regular Expressions

- ▶ `/(Ruby){3}/`
 - `{“RubyRubyRuby”}`
 - `{x}` means repeat the search for **exactly** x occurrences
- ▶ `/(Ruby){3,}/`
 - `{“RubyRubyRuby”, “RubyRubyRubyRuby”, ...}`
 - `{x,}` means repeat the search for **at least** x occurrences
- ▶ `/(Ruby){3, 5}/`
 - `{“RubyRubyRuby”, “RubyRubyRubyRuby”, “RubyRubyRubyRubyRuby”}`
 - `{x, y}` means repeat the search for at least x occurrences and at most y occurrences

Watch Out for Precedence

- ▶ `/(Ruby)*/` means `{ "", "Ruby", "RubyRuby", ... }`
- ▶ `/Ruby*/` means `{ "Rub", "Ruby", "Rubyy", ... }`
- ▶ In general
 - `*` `{n}` and `+` bind most tightly
 - Then concatenation (adjacency of regular expressions)
 - Then `|`
- ▶ Best to use parentheses to disambiguate
 - Note that parentheses have another use, to extract matches, as we'll see later

Character Classes

- ▶ `/[abcd]/`
 - `{"a", "b", "c", "d"}` (Can you write this another way?)
- ▶ `/[a-zA-Z0-9]/`
 - Any upper or lower case letter or digit
- ▶ `/[^0-9]/`
 - Any character except 0-9 (the ^ is like not and must come first)
- ▶ `/[\t\n]/`
 - Tab, newline or space
- ▶ `/[a-zA-Z_\\$][a-zA-Z_\\$0-9]*/`
 - Java identifiers (\$ escaped...see next slide)

Special Characters

.	any character	Using <code>/^pattern\$/</code> ensures entire string/line must match pattern
^	beginning of line	
\$	end of line	
\\$	just a \$	
\d	digit, [0-9]	
\s	whitespace, [\t\r\n\f\s]	
\w	word character, [A-Za-z0-9_]	
\D	non-digit, [^0-9]	
\S	non-space, [^\t\r\n\f\s]	
\W	non-word, [^A-Za-z0-9_]	

Potential Character Class Confusions

- ▶ ^
 - Inside character classes: *not*
 - Outside character classes: beginning of line
- ▶ []
 - Inside regular expressions: character class
 - Outside regular expressions: array
 - Note: [a-z] does not make a valid array
- ▶ ()
 - Inside character classes: literal characters ()
 - Note /(0..2)/ does not mean 012
 - Outside character classes: used for grouping
- ▶ —
 - Inside character classes: range (e.g., a to z given by [a-z])
 - Outside character classes: subtraction

Summary

- ▶ Let *re* represents an arbitrary pattern; then:
 - */re/* – matches regexp *re*
 - */(re₁|re₂)/* – match either *re₁* or *re₂*
 - */(re)*/* – match 0 or more occurrences of *re*
 - */(re)+/* – match 1 or more occurrences of *re*
 - */(re)?/* – match 0 or 1 occurrences of *re*
 - */(re){2}/* – match exactly two occurrences of *re*
 - */[a-z]/* – same as *(a|b|c|...|z)*
 - */[^0-9]/* – match any character that is not 0, 1, etc.
 - *^*, *\$* – match start or end of string

Try out regexps at rubular.com

Rubular
a Ruby regular expression editor

Your regular expression:
/[CMSC]\d+ /

Your test string:
C222

Match result:
C222

Wrap words ☒ Show invisibles ☐ Ruby version 2.1.5

[make permalink](#) [clear fields](#)

Regular Expression Practice

Contains 3 b's, may not be consecutive.

$$/^{\wedge}[\wedge b]^*b[\wedge b]^*b[\wedge b]^*b[\wedge b]^*\$/$$

Regular Expression Practice

- ▶ Starts with c, followed by one vowel, and any number of letters

`/^c[aouei][a-z]*$/`

Regular Expression Practice

- ▶ All letters are in alphabetic order

`/^a*b*c*d*e*f*g*h*i*j*k*l*m*n*o*p*r*t*$`

Regular Expression Practice

- ▶ Contains sss or ccc

$/s\{3\}|c\{3\}/$

Regular Expression Practice

- ▶ contains 2 ab

$/(ab)\{2\}/$

- ▶ contains 2 b

$/b\{2\}/$

Regular Expression Practice

- ▶ Starts with a, 0 or 1 letter after that

$/^a[a-z]?$/$

Regular Expression Practice

- ▶ Contains one or more ab or ba

$/(ab|ba)^+/$

Regular Expression Practice

- ▶ steve, steven, or stephen

`/^ste(ve|phen|ven)$/`

Regular Expression Practice

- ▶ Even length string

$$/^{\wedge}(\cdot\cdot)^{*}\$/$$$

Regular Expression Practice

- ▶ Even number of vowels

$$/^([\text{aouei}]^*[\text{aouei}][\text{aouei}]^*[\text{aouei}][\text{aouei}]^*)^*\$/$$

Regular Expression Practice

- ▶ starts with not-b, 0 or more times of any number of b followed by one not-b

$$/^{\wedge}[\wedge b]^+(b+[\wedge b])^*/$$

Regular Expression Practice

- ▶ Make Ruby regular expressions representing
 - All lines beginning with a or b `/^(a|b)/`
 - All lines containing at least two (only alphabetic) words separated by white-space `/[a-zA-Z]^+\s+[a-zA-Z]^+/$`
 - All lines where a and b alternate and appear at least once `/^((ab)^+a?)|((ba)^+b?)$/`
 - An expression which would match both of these lines (but not radically different ones)
 - CMSC330: Organization of Programming Languages: Fall 2018
 - CMSC351: Algorithms: Fall 2018

Quiz 1

How many different strings could this regex match?

`/^Hello, Anyone awake?$/`

- A. 1
- B. 2
- C. 4
- D. More than 4

Quiz 1

How many different strings could this regex match?

e or nothing

`/^Hello, Anyone awake?e?$ /`

- A. 1
- B. 2**
- C. 4
- D. More than 4

Quiz 2

Which regex is **not** equivalent to the others?

- A. `^[crab]$`
- B. `^c?r?a?b?$`
- C. `^(c|r|a|b)$`
- D. `^([cr]|[ab])$`

Quiz 2

Which regex is **not** equivalent to the others?

- A. `^[crab]$`
- B. `^c?r?a?b?$`
- C. `^(c|r|a|b)$`
- D. `^([cr]|[ab])$`

Quiz 3

Which string does **not** match the regex?

`/[a-z]{4}\d{3}/`

- A. `"cm\sc\d\d\d"`
- B. `"cm\sc330"`
- C. `"hello\cm\sc330"`
- D. `"cm\sc330world"`

Quiz 3

Which string does **not** match the regex?

*Recall that without $^$ and $\$$, a regex will match any **substring***

`/[a-z]{4}\d{3}/`

- A. **`"cm\sc\d\d\d"`**
- B. **`"cm\sc330"`**
- C. **`"hell\ocm\sc330"`**
- D. **`"cm\sc330world"`**

Extracting Substrings based on R.E.'s

Method 1: Back References

Two options to extract substrings based on R.E.'s:

► Use **back references**

- Ruby remembers which strings matched the parenthesized parts of r.e.'s
- These parts can be referred to using special variables called back references (named \$1, \$2,...)

Back Reference Example

```
gets =~ /^Min: (\d+) Max: (\d+)$/
min, max = $1, $2
puts "mini=#{min} maxi=#{max}"
```

```
sets min = $1
and max = $2
```

► Input

Min: 1 Max: 27

Min: 10 Max: 30

Min: 11 Max: 30

Min: a Max: 24

► Output

mini=1 maxi=27

mini=10 maxi=30

mini= maxi=

mini= maxi=

Extra space messes up match

Not a digit; messes up match

Back References are Local

► Warning

- Despite their names, \$1 etc are **local** variables
- (Normally, variables starting with \$ are global)

```
def m(s)
  s =~ /(Foo)/
  puts $1    # prints Foo
end
m("Foo")
puts $1      # prints nil
```

Back References are Reset

► Warning 2

- If another search is performed, all back references are **reset** to nil

```
gets =~ /(h)e(ll)o/  
puts $1  
puts $2  
gets =~ /h(e)llo/  
puts $1  
puts $2  
gets =~ /hello/  
puts $1
```

```
hello  
h  
ll  
hello  
e  
nil  
hello  
nil
```

Quiz 4

What is the output of the following code?

```
s = "help I'm stuck in a text editor"  
s =~ /([A-Z]+)/  
puts $1
```

- A. help
- B. I
- C. I'm
- D. I'm stuck in a text editor

Quiz 4

What is the output of the following code?

```
s = "help I'm stuck in a text editor"  
s =~ /([A-Z]+)/  
puts $1
```

- A. help
- B. I
- C. I'm
- D. I'm stuck in a text editor

Quiz 5

What is the output of the following code?

```
"Why was 6 afraid of 7?" =~ /\d\s(\w+) .*(\d) /  
puts $2
```

- A. afraid
- B. Why
- C. 6
- D. 7

Quiz 5

What is the output of the following code?

```
"Why was 6 afraid of 7?" =~ /\d\s(\w+) .*(\d) /  
puts $2
```

- A. afraid
- B. Why
- C. 6
- D. 7

Method 2: String.scan

- ▶ Also extracts substrings based on regular expressions
- ▶ Can optionally use parentheses in regular expression to affect how the extraction is done
- ▶ Has two forms that differ in what Ruby does with the matched substrings
 - The first form returns an array
 - The second form uses a code block
 - We'll see this later

First Form of the Scan Method

► `str.scan(regex)`

- If `regex` doesn't contain any parenthesized subparts, returns an array of matches

► An array of all the substrings of `str` which matched

```
s = "CMSC 330 Fall 2018"  
s.scan(/\S+ \S+/  
# returns array ["CMSC 330", "Fall 2018"]
```

► Note: these strings are chosen sequentially from as yet unmatched portions of the string, so while “330 Fall” does match the regular expression above, it is *not* returned since “330” has already been matched by a previous substring.

```
s.scan(/\S{2}/)  
# => ["CM", "SC", "33", "Fa", "11", "20", "18"]
```

First Form of the Scan Method (cont.)

- If `regexp` contains parenthesized subparts, returns an array of arrays
 - Each sub-array contains the parts of the string which matched one occurrence of the search

```
s = "CMSC 330 Fall 2018"
s.scan(/(\S+) (\S+)/) # [["CMSC", "330"],
                        # ["Fall", "2018"]]
```

- Each sub-array has the same number of entries as the number of parenthesized subparts
- All strings that matched the first part of the search (or `$1` in back-reference terms) are located in the first position of each sub-array

Practice with Scan and Back-references

```
> ls -l
```

```
drwx----- 2 sorelle sorelle 4096 Feb 18 18:05 bin
-rw----- 1 sorelle sorelle 674 Jun 1 15:27 calendar
drwx----- 3 sorelle sorelle 4096 May 11 2006 cmsc311
drwx----- 2 sorelle sorelle 4096 Jun 4 17:31 cmsc330
drwx----- 1 sorelle sorelle 4096 May 30 19:19 cmsc630
drwx----- 1 sorelle sorelle 4096 May 30 19:20 cmsc631
```

Extract just the file or directory name from a line using

- scan

```
name = line.scan(/\S+$/) # ["bin"]
```

- back-references

```
if line =~ /\S+$/
  name = $1 # "bin"
end
```

Quiz 6

What is the output of the following code?

```
s = "Hello World"  
t = s.scan(/\w{2}/).length  
puts t
```

- A. 3
- B. 4
- C. 5
- D. 6

Quiz 6

What is the output of the following code?

```
s = "Hello World"  
t = s.scan(/\w{2}/).length  
puts t
```

- A. 3
- B. 4
- C. 5
- D. 6

Quiz 7

What is the output of the following code?

```
s = "To be, or not to be!"  
a = s.scan(/(\S+) (\S+)/)  
puts a.inspect
```

- A. ["To", "be,", "or", "not", "to", "be!"]
- B. [["To", "be,", "or", "not"], ["to", "be!"]]
- C. ["To", "be,"]
- D. ["to", "be!"]

Quiz 7

What is the output of the following code?

```
s = "To be, or not to be!"  
a = s.scan(/(\S+) (\S+)/)  
puts a.inspect
```

- A. ["To", "be,", "or", "not", "to", "be!"]
- B. [["To", "be,",], ["or", "not"], ["to", "be!"]]
- C. ["To", "be,"]
- D. ["to", "be!"]

Second Form of the Scan Method

- ▶ Can take a **code block** as an optional argument
- ▶ `str.scan(regex) { |match| block }`
 - Applies the code block to each match
 - Short for `str.scan(regex).each { |match| block }`
 - The regular expression can also contain parenthesized subparts

Example of Second Form of Scan

12	34	23
19	77	87
11	98	3
2	45	0

input file:
will be read line by line, but
column summation is desired

```
sum_a = sum_b = sum_c = 0
while (line = gets)
    line.scan(/(\d+)\s+(\d+)\s+(\d+)/) { |a,b,c|
        sum_a += a.to_i
        sum_b += b.to_i
        sum_c += c.to_i
    }
end
printf("Total: %d %d %d\n", sum_a, sum_b, sum_c)
```

converts the string
to an integer

Sums up three columns of numbers

Practice: Amino Acid counting in DNA

Write a function that will take a filename and read through that file counting the number of times each group of three letters appears so these numbers can be accessed from a hash.

(assume: the number of chars per line is a multiple of 3)

```
gcggcattcagcacccgtatactgttaagcaatccagatTTTTgtgtataacataccggc
catactgaagcattcattgaggctagcgctgataacagtagcgctaacaatggggggaatg
tggcaatacgggtgcgattactaagagccgggaccacacaccccgtaaggatggagcgtgg
taacataataatccggttcaagcagtgggcgaagggtggagatggtccagtaagaatagtg
gggcctactacccatggtacataattaagagatcgtcaatcttgagacgggtcaatggtac
cgagactatatcactcaactccggacgtatgcgcttactgggtcacctcgttactgacgga
```

Practice: Amino Acid counting in DNA

get the
file
handle

array of
lines
from the
file

for each
line in
the file

for each
triplet
in the
line

```
def countaa(filename)
  file = File.new(filename, "r")
  lines = file.readlines
  hash = Hash.new
  lines.each{ |line|
    acids = line.scan(/.../)
    acids.each{ |aa|
      if hash[aa] == nil
        hash[aa] = 1
      else
        hash[aa] += 1
      end
    }
  }
end
```

initialize
the hash, or
you will get
an error when
trying to
index into an
array with a
string

get an array
of triplets
in the line