

CMSC 132: OBJECT-ORIENTED PROGRAMMING II



Networking

Department of Computer Science
University of Maryland, College Park

Networking

- **Internet**
 - Designed with multiple layers of abstraction
 - Underlying medium is unreliable, packet oriented
 - Packet-Switching
 - <https://www.youtube.com/watch?v=vSlcoQowe9I>

Internet (IP) Address

- **Unique address for machine on the internet**
 - Get from ISP when connecting to internet
 - Allows network to find your machine
- **Internet Protocols IPV4, IPV6**
 - Define how data is sent between computers over packet-switched network
- **(IPV4) Internet Protocol Version 4**
 - 32-bit unsigned integer \Rightarrow 128.8.128.8
 - Domain name \Rightarrow cs.umd.edu
- **(IPV6) Internet Protocol Version 6**
 - 128-bit address
 - Designed to replace IPV4
 - Addresses exhaustion of addresses associated with IPV4 (now we have 2^{128})
 - <https://en.wikipedia.org/wiki/IPv6>

IP Address (DNS)

- Domain Name System (DNS)
 - Protocol for translating domain names to IP addresses
 - Example: cs.umd.edu → 128.8.128.44
 - Multiple DNS servers on internet
 - DNS server may need to query other DNS servers
 - edu DNS server queries umd.edu server to find cs.umd.edu

Ports

- Abstraction to identify (refine) destination
 - Provide multiple destinations at single IP address
- IP Address (identifies computer) and port number identifies program/resource in the computer
- A port is an unsigned 16-bit integer (0 to 65,535)
- Many ports pre-assigned to important services
 - 21 ftp (file transfer)
 - 23 telnet (remote terminal)
 - 25 SMTP (email)
 - **80** http (web)
 - Others
 - http://en.wikipedia.org/wiki/List_of_TCP_and_UDP_port_numbers

Uniform Resource Identifier (URIs)

- Consists of
 - Scheme
 - http:
 - https: (secure http)
 - mailto:
 - IP address (or domain name)
 - Port (optional, 80 if not specified)
 - http://www.cs.umd.edu:80/
 - Reference to anchor (optional)
 - Query terms
- URL (Uniform Resource Locator) → specific type of URI

Internet Connections

- Two types of connections: **TCP** and **UDP**
- **TCP**
 - Connection oriented
 - Provides reliable connection
 - **Examples:** ftp, ssh, http
 - **Vast majority of internet traffic is TCP**
- **UDP**
 - More like sending a postcard
 - Might get lost with no notification
 - Useful in some specialized cases
 - Messages are small
 - if a packet is lost, would rather just lose it than delay receipt of next packet

Java Networking Examples

- Network I/O: See `networkIO` package
- TCP Client/Server: See `tcpServerClient` package
- Toy Web Server: See `toyWebServer` package