

Final Exam

*Open book and notes; In class**Tuesday, December 18th*

- ⊕ *Do not forget to write your name on the first page. Initial each subsequent page.*
- ⊕ *Be **neat and precise**. I will not grade answers I cannot read.*
- ⊕ *You should draw simple figures if you think it will make your answers clearer.*
- ⊕ *Good luck and remember, brevity is the soul of wit*

- All problems are mandatory
- I cannot stress this point enough: **Be precise**. If you have written something incorrect along with the correct answer, you should **not** expect to get all the points. I will grade based upon what you **wrote**, not what you **meant**.
- Maximum possible points: 50.

Name: _____

Problem	Points
1	
2	
3	
4	
5	
Total	

1. Nomenclature

(a) Describe the following: (2 points each)

- Multiple Access Protocol

- Name Server

- Consistent Hashing

- URGENT flag in TCP

- Error polynomial in CRC

4. Applications and Naming

(a) List two problems with how the original HTTP protocol interacted with TCP/IP. (2 points)

(b) What is the TURN command in SMTP used for? (2 points)

(c) Suppose your HTTP request is served by a CDN. What information about your client does the CDN DNS server receive? (3 points)

(d) Does DNS provide a mechanism for root DNS servers to change their IP addresses? Describe the procedure or state what the primary difficulty is. (3 points)

5. General

- (a) The CRC-32 polynomial $x^{32} + x^{26} + x^{23} + x^{22} + x^{16} + x^{12} + x^{11} + x^{10} + x^8 + x^7 + x^5 + x^4 + x^2 + x + 1$ is used in Ethernet. How would you show that this CRC-polynomial can detect all odd number of bit errors? (2 points)
- (b) The *Hamming Distance* between two bit strings A and B is the number of bits that have to be changed in A to obtain B. Prove the following statement or disprove it with a counter example: “The minimum Hamming distance between two valid messages using the CRC-32 polynomial above is 16”. (3 points)
- (c) How are BitCoin peers notified of new transactions? (2 points)
- (d) How would BitTorrent be affected if all the SHA-1 hashes in the protocol were replaced by CRCs? (3 points)