

Problem Set #4

Quantum Error Correction
Instructors: Daniel Gottesman

Due Tuesday, Apr. 14, 2026

General instructions: No use of LLMs. If you collaborate or use any outside resources, remember to cite them in your solutions.

Problem #1. Repetition of syndrome measurement in Shor error correction (40 points)

For Shor error correction and a distance 3 code, consider the following method of repeated syndrome measurement: Measure the error syndrome twice. If both syndrome measurements are the same, use that value. If the syndrome measurements differ but the first syndrome measured is 0 (corresponding to no error), deduce the trivial error. If the syndrome measurements differ but the first syndrome is non-zero, use the second syndrome to deduce the error.

- (15 points) Show that this method of repeating the syndrome and deducing the error satisfies the ECCP for a code correcting 1 error.
- (15 points) For the 7-qubit code, show that the ECRP is not satisfied by giving a combination of an error on the input state to the EC gadget and a fault during the gadget that cause the ECRP to fail.
- (10 points) For the 5-qubit code, show that the ECRP is satisfied.

Problem #2. Teleportation of the controlled-phase gate (20 points)

Let U be the gate

$$U = \begin{pmatrix} 1 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 \\ 0 & 0 & 1 & 0 \\ 0 & 0 & 0 & i \end{pmatrix}. \quad (1)$$

- (5 points) Find UPU^\dagger for $P = X \otimes I, I \otimes X, Z \otimes I,$ and $I \otimes Z$.
- (15 points) Find a *two-qubit* ancilla state and a circuit involving two data qubits and the ancilla consisting of Clifford group gates, Pauli basis measurements, and classical feed-forward, such that the output of the circuit is $U|\psi\rangle$. ($|\psi\rangle$ is the input state of the two data qubits.)