CMSC 330: Organization of Programming Languages

Operational Semantics

Formal Semantics of a Prog. Lang.

- Mathematical description of the meaning of programs written in that language
  - What a program computes, and what it does

- Three main approaches to formal semantics
  - Denotational
  - Operational
  - Axiomatic

Styles of Semantics

- Denotational semantics: translate programs into math!
  - Usually: convert programs into functions mapping inputs to outputs
  - Analogous to compilation
- Operational semantics: define how programs execute
  - Often on an abstract machine (mathematical model of computer)
  - Analogous to interpretation
- Axiomatic semantics
  - Describe programs as predicate transformers, i.e. for converting initial assumptions into guaranteed properties after execution
    - Preconditions: assumed properties of initial states
    - Postcondition: guaranteed properties of final states
  - Logical rules describe how to systematically build up these transformers from programs

This Course: Operational Semantics

- We will show how an operational semantics may be defined for Micro-Ocaml
  - And develop an interpreter for it, along the way

- Approach: use rules to define a judgment

$$e \Rightarrow v$$

  - Says "***e*** *evaluates to* ***v***"
  - ***e***: expression in Micro-OCaml
  - ***v***: value that results from evaluating ***e***

Definitional Interpreter

- It turns out that the rules for judgment $e \Rightarrow v$ can be easily turned into idiomatic OCaml code
  - The language's expressions e and values v have corresponding OCaml datatype representations `exp` and `value`
  - The semantics is represented as a function

```
eval: exp -> value
```

- This way of presenting the semantics is referred to as a definitional interpreter
  - The interpreter defines the language's meaning

Micro-OCaml Expression Grammar

e ::= ***x*** | ***n*** | ***e*** **+** ***e*** | **`let`** ***x*** **=** ***e*** **`in`** ***e***

- ***e***, ***x***, ***n*** are *meta-variables* that stand for categories of syntax
  - ***x*** is any identifier (like **`z`**, **`y`**, **`foo`**)
  - ***n*** is any numeral (like **`1`**, **`0`**, **`10`**, **`-25`**)
  - ***e*** is any expression (here defined, recursively!)

- *Concrete syntax* of actual expressions in **black**
  - Such as **`let`**, **`+`**, **`z`**, **`foo`**, **`in`**, …

- ::= and | are *meta-syntax* used to define the syntax of a language (part of "Backus-Naur form," or BNF)

Micro-OCaml Expression Grammar

$$e ::= x \mid n \mid e + e \mid \texttt{let}\ x\ \texttt{=}\ e\ \texttt{in}\ e$$

- Examples
  - `1` is a numeral ***n*** which is an expression ***e***
  - `1+z` is an expression ***e*** because
    - `1` is an expression ***e***,
    - `z` is an identifier ***x***, which is an expression ***e***, and
    - ***e*** + ***e*** is an expression ***e***
  - `let z = 1 in 1+z` is an expression ***e*** because
    - `z` is an identifier ***x***,
    - `1` is an expression ***e*** ,
    - `1+z` is an expression ***e***, and
    - `let` ***x*** `=` ***e*** `in` ***e*** is an expression ***e***

Abstract Syntax = Structure

- Here, the grammar for ***e*** is describing its abstract syntax tree (AST), i.e., ***e***'s structure

$$e ::= x \mid n \mid e + e \mid \texttt{let}\ x\ \texttt{=}\ e\ \texttt{in}\ e$$

corresponds to (in defn interpreter)

```
type id = string
type num = int
type exp =
   | Ident of id
   | Num of num
   | Plus of exp * exp
   | Let of id * exp * exp
```

Parsing (deferred)

- The parsing problem is how to convert program text into an AST, i.e., a value of the type below
  - We defer worrying about this problem until later
    - Hint: Relates to using something like regular expressions to read in text and construct values like the following from it

```
type id = string
type num = int
type exp =
   | Ident of id
   | Num of num
   | Plus of exp * exp
   | Let of id * exp * exp
```

Values

- An expression's final result is a value. What can values be?

$$v ::= n$$

- Just numerals for now
  - In terms of an interpreter's representation:

```
type value = int
```

  - In a full language, values ***v*** will also include booleans (**`true`**, **`false`**), strings, functions, …

Defining the Semantics

- Use rules to define judgment ***e*** ⇒ ***v***
- These rules will allow us to show things like
  - **`1+3`** ⇒ **`4`**
    - **`1+3`** is an expression ***e***, and **`4`** is a value ***v***
    - This judgment claims that **`1+3`** evaluates to **`4`**
    - We use rules to prove it to be true
  - **`let foo=1+2 in foo+5`** ⇒ **`8`**
  - **`let f=1+2 in let z=1 in f+z`** ⇒ **`4`**

Rules as English Text

No rule for ***x***

- Suppose ***e*** is a numeral ***n***
  - Then ***e*** evaluates to itself, i.e., ***n*** ⇒ ***n***
- Suppose ***e*** is an addition expression ***e1*** + ***e2***
  - If ***e1*** evaluates to ***n1***, i.e., ***e1*** ⇒ ***n1***
  - If ***e2*** evaluates to ***n2***, i.e., ***e2*** ⇒ ***n2***
  - Then ***e*** evaluates to ***n3***, where ***n3*** is the sum of ***n1*** and ***n2***
  - I.e., ***e1*** + ***e2*** ⇒ ***n3***
- Suppose ***e*** is a let expression `let` ***x*** `=` ***e1*** `in` ***e2***
  - If ***e1*** evaluates to ***v***, i.e., ***e1*** ⇒ ***v1***
  - If ***e2{v1/x}*** evaluates to ***v2***, i.e., ***e2{v1/x}*** ⇒ ***v2***
    - Here, ***e2{v1/x}*** means "the expression after substituting occurrences of ***x*** in ***e2*** with ***v1***"
  - Then ***e*** evaluates to ***v2***, i.e., `let` ***x*** `=` ***e1*** `in` ***e2*** ⇒ ***v2***

Rules of Inference

- We can use a more compact notation for the rules we just presented: rules of inference
  - Has the following format

$$\frac{H_1 \quad \ldots \quad H_n}{C}$$

  - Says: if the conditions $H_1 \quad \ldots \quad H_n$ ("hypotheses") are true, then the condition C ("conclusion") is true
  - If n=0 (no hypotheses) then the conclusion automatically holds; this is called an axiom
- We will use inference rules to speak about evaluation

Rules of Inference: Num and Sum

- Suppose ***e*** is a numeral ***n***
  - Then ***e*** evaluates to itself, i.e., ***n*** ⇒ ***n***

$$\frac{}{n \Rightarrow n}$$

- Suppose ***e*** is an addition expression ***e1*** + ***e2***
  - If ***e1*** evaluates to ***n1***, i.e., ***e1*** ⇒ ***n1***
  - If ***e2*** evaluates to ***n2***, i.e., ***e2*** ⇒ ***n2***
  - Then ***e*** evaluates to ***n3***, where ***n3*** is the sum of ***n1*** and ***n2***
  - I.e., ***e1*** + ***e2*** ⇒ ***n3***

$$\frac{e1 \Rightarrow n1 \qquad e2 \Rightarrow n2 \qquad n3 \text{ is } n1+n2}{e1 + e2 \Rightarrow n3}$$

Rules of Inference: Let

- Suppose ***e*** is a let expression `let` ***x*** `=` ***e1*** `in` ***e2***
  - If ***e1*** evaluates to ***v***, i.e., ***e1*** ⇒ ***v1***
  - If ***e2{v1/x}*** evaluates to ***v2***, i.e., ***e2{v1/x}*** ⇒ ***v2***
  - Then ***e*** evaluates to ***v2***, i.e., `let` ***x*** `=` ***e1*** `in` ***e2*** ⇒ ***v2***

$$\frac{e1 \Rightarrow v1 \qquad e2\{v1/x\} \Rightarrow v2}{\texttt{let}\ x\ \texttt{=}\ e1\ \texttt{in}\ e2 \Rightarrow v2}$$

Derivations

- When we apply rules to an expression in succession, we produce a derivation
  - It's a kind of tree, rooted at the conclusion

- Produce a derivation by goal-directed search
  - Pick a rule that could prove the goal
  - Then repeatedly apply rules on the corresponding hypotheses
    - Goal: Show that `let x = 4 in x+3` $\Rightarrow$ `7`

Derivations

$$\frac{}{n \Rightarrow n}$$

$$\frac{e1 \Rightarrow n1 \qquad e2 \Rightarrow n2 \qquad n3 \text{ is } n1+n2}{e1 + e2 \Rightarrow n3}$$

$$\frac{e1 \Rightarrow v1 \qquad e2\{v1/x\} \Rightarrow v2}{\texttt{let } x \texttt{ = } e1 \texttt{ in } e2 \Rightarrow v2}$$

Goal: show that
`let x = 4 in x+3` $\Rightarrow$ `7`

$$\frac{\dfrac{}{4 \Rightarrow 4} \qquad \dfrac{\dfrac{}{4 \Rightarrow 4} \qquad \dfrac{}{3 \Rightarrow 3} \qquad 7 \text{ is } 4+3}{4+3 \Rightarrow 7}}{\texttt{let x = 4 in x+3} \Rightarrow 7}$$

Quiz 1

What is derivation of the following judgment?

$$2 + (3 + 8) \Rightarrow 13$$

```
(a)
2 ⇒ 2      3 + 8 ⇒ 11
-----------------------
2 + (3 + 8) ⇒ 13
```

```
(b)
3 ⇒ 3    8 ⇒ 8
-------------
3 + 8 ⇒ 11                2 ⇒ 2
---------------------------------
2 + (3 + 8) ⇒ 13
```

```
(c)
          8 ⇒ 8
          3 ⇒ 3
          11 is 3+8
          ----------
2 ⇒ 2     3 + 8 ⇒ 11     13 is 2+11
-------------------------------------
2 + (3 + 8) ⇒ 13
```

Quiz 1

What is derivation of the following judgment?

$$2 + (3 + 8) \Rightarrow 13$$

```
(a)
2 ⇒ 2      3 + 8 ⇒ 11
-----------------------
2 + (3 + 8) ⇒ 13
```

```
(b)
3 ⇒ 3    8 ⇒ 8
------------
3 + 8 ⇒ 11                2 ⇒ 2
---------------------------------
2 + (3 + 8) ⇒ 13
```

```
(c)
          8 ⇒ 8
          3 ⇒ 3
          11 is 3+8
          -----------
2 ⇒ 2     3 + 8 ⇒ 11     13 is 2+11
-------------------------------------
2 + (3 + 8) ⇒ 13
```

Definitional Interpreter

Trace of evaluation of **`eval`** function corresponds to a derivation by the rules

- The style of rules lends itself directly to the implementation of an interpreter as a recursive function

```
let rec eval (e:exp):value =
  match e with
    Ident x -> (* no rule *)
     failwith "no value"
  | Num n -> n
  | Plus (e1,e2) ->
     let n1 = eval e1 in
     let n2 = eval e2 in
     let n3 = n1+n2 in
     n3
  | Let (x,e1,e2) ->
     let v1 = eval e1 in
     let e2′ = subst v1 x e2 in
     let v2 = eval e2′ in v2
```

$$\frac{}{n \Rightarrow n}$$

$$\frac{e1 \Rightarrow n1 \qquad e2 \Rightarrow n2 \qquad n3 \text{ is } n1+n2}{e1 + e2 \Rightarrow n3}$$

$$\frac{e1 \Rightarrow v1 \qquad e2\{v1/x\} \Rightarrow v2}{\texttt{let } x \texttt{ = } e1 \texttt{ in } e2 \Rightarrow v2}$$

Derivations = Interpreter Call Trees

$$\frac{4 \Rightarrow 4 \qquad \dfrac{4 \Rightarrow 4 \qquad 3 \Rightarrow 3 \qquad 7 \text{ is } 4+3}{4+3 \Rightarrow 7}}{\texttt{let x = 4 in x+3} \Rightarrow 7}$$

Has the same shape as the recursive call tree of the interpreter:

$$\frac{\texttt{eval Num 4} \Rightarrow 4 \qquad \dfrac{\texttt{eval Num 3} \Rightarrow 3 \qquad 7 \text{ is } 4+3}{\texttt{eval (subst 4 "x" Plus(Ident("x"),Num 3))} \Rightarrow 7}}{\texttt{eval Let("x",Num 4,Plus(Ident("x"),Num 3))} \Rightarrow 7}$$

Semantics Defines Program Meaning

- ***e*** ⇒ ***v*** holds if and only if a *proof* can be built
  - Proofs are derivations: axioms at the top, then rules whose hypotheses have been proved to the bottom
  - No proof means ***e*** ⇏ ***v***
- Proofs can be constructed bottom-up
  - In a goal-directed fashion
- Thus, function eval ***e*** = {***v*** | ***e*** ⇒ ***v***}
  - Determinism of semantics implies at most one element for any ***e***
- So: Expression ***e*** *means* ***v***

Environment-style Semantics

- The previous semantics uses substitution to handle variables
  - As we evaluate, we replace all occurrences of a variable `x` with values it is bound to
- An alternative semantics, closer to a real implementation, is to use an environment
  - As we evaluate, we maintain an explicit map from variables to values, and look up variables as we see them

Environments

- Mathematically, an environment is a partial function from identifiers to values
  - If A is an environment, and ***x*** is an identifier, then A(***x***) can either be …
  - … a value (intuition: the variable has been declared)
  - … or undefined (intuition: variable has not been declared)
- An environment can also be thought of as a table
  - If A is

Id	Val
`x`	0
`y`	2

  - then A(`x`) is `0`, A(`y`) is `2`, and A(`z`) is undefined

Notation, Operations on Environments

- • is the empty environment (undefined for all ids)
- ***x***:***v*** is the environment that maps ***x*** to ***v*** and is undefined for all other ids
- If A and A' are environments then A, A' is the environment defined as follows

$$(A, A')(\boldsymbol{x}) = \begin{cases} A'(\boldsymbol{x}) & \text{if } A'(\boldsymbol{x}) \text{ defined} \\ A(\boldsymbol{x}) & \text{if } A'(\boldsymbol{x}) \text{ undefined but } A(\boldsymbol{x}) \text{ defined} \\ \text{undefined} & \text{otherwise} \end{cases}$$

- So: A' *shadows* definitions in A
- For brevity, can write •, A as just A

Semantics with Environments

- The environment semantics changes the judgment

$$e \Rightarrow v$$

to be

$$A;\ e \Rightarrow v$$

where A is an environment
  - Idea: A is used to give values to the identifiers in *e*
  - A can be thought of as containing declarations made up to *e*
- Previous rules can be modified by
  - Inserting A everywhere in the judgments
  - Adding a rule to look up variables *x* in A
  - Modifying the rule for `let` to add *x* to A

Environment-style Rules

$$\frac{A(x) = v}{A;\ x \Rightarrow v}$$

Look up variable ***x*** in environment A

$$\frac{}{A;\ n \Rightarrow n}$$

$$\frac{A;\ e1 \Rightarrow v1 \qquad A, x{:}v1;\ e2 \Rightarrow v2}{A;\ \texttt{let}\ x\ \texttt{=}\ e1\ \texttt{in}\ e2 \Rightarrow v2}$$

Extend environment A with mapping from ***x*** to ***v1***

$$\frac{A;\ e1 \Rightarrow n1 \qquad A;\ e2 \Rightarrow n2 \qquad n3 \text{ is } n1+n2}{A;\ e1 + e2 \Rightarrow n3}$$

Quiz 2

What is a derivation of the following judgment?

```
•; let x=3 in x+2 ⇒ 5
```

(a)

```
        x ⇒ 3    2 ⇒ 2   5 is 3+2
        --------------------
3 ⇒ 3     x+2 ⇒ 5
-------------------------
let x=3 in x+2 ⇒ 5
```

(c)

```
x:2; x⇒3   x:2; 2⇒2   5 is 3+2
-----------------------------
•; let x=3 in x+2 ⇒ 5
```

(b)

```
           x:3; x ⇒ 3   x:3; 2 ⇒ 2    5 is 3+2
           -------------------------------
•;3 ⇒ 3     x:3; x+2 ⇒ 5
-----------------------
•; let x=3 in x+2 ⇒ 5
```

Quiz 2

What is a derivation of the following judgment?

```
•; let x=3 in x+2 ⇒ 5
```

(a)

```
        x ⇒ 3    2 ⇒ 2   5 is 3+2
        --------------------
3 ⇒ 3     x+2 ⇒ 5
-------------------------
let x=3 in x+2 ⇒ 5
```

(c)

```
x:2; x⇒3   x:2; 2⇒2   5 is 3+2
-----------------------------
•; let x=3 in x+2 ⇒ 5
```

(b)

```
          x:3; x ⇒ 3   x:3; 2 ⇒ 2    5 is 3+2
        -------------------------------
•;3 ⇒ 3     x:3; x+2 ⇒ 5
-------------------------
•; let x=3 in x+2 ⇒ 5
```

Definitional Interpreter: Environments

```
type env = (id * value) list

let extend env x v = (x,v)::env

let rec lookup env x =
  match env with
    [] -> failwith "no var"
  | (y,v)::env' ->
    if x = y then v
    else lookup env' x
```

Definitional Interpreter: Evaluation

```
let rec eval env e =
  match e with
    Ident x -> lookup env x
  | Num n -> n
  | Plus (e1,e2) ->
     let n1 = eval env e1 in
     let n2 = eval env e2 in
     let n3 = n1+n2 in
     n3
  | Let (x,e1,e2) ->
     let v1 = eval env e1 in
     let env' = extend env x v1 in
     let v2 = eval env' e2 in v2
```

Adding Conditionals to Micro-OCaml

$e ::= x \mid v \mid e + e \mid \texttt{let } x \texttt{ = } e \texttt{ in } e$
$\mid \texttt{eq0 } e \mid \texttt{if } e \texttt{ then } e \texttt{ else } e$

$v ::= n \mid \texttt{true} \mid \texttt{false}$

- In terms of interpreter definitions:

```
type exp =
  | Val of value
  | … (* as before *)
  | Eq0 of exp
  | If of exp * exp * exp
```

```
type value =
    Int of int
  | Bool of bool
```

Rules for Eq0 and Booleans

$$\frac{}{A;\ \texttt{true} \Rightarrow \texttt{true}}$$

$$\frac{A;\ e \Rightarrow 0}{A;\ \texttt{eq0}\ e \Rightarrow \texttt{true}}$$

$$\frac{}{A;\ \texttt{false} \Rightarrow \texttt{false}}$$

$$\frac{A;\ e \Rightarrow v \qquad v \neq 0}{A;\ \texttt{eq0}\ e \Rightarrow \texttt{false}}$$

- Booleans evaluate to themselves
  - A; `false` ⇒ `false`
- `eq0` tests for `0`
  - A; `eq0 0` ⇒ `true`
  - A; `eq0 3+4` ⇒ `false`

Rules for Conditionals

$$\frac{A;\ e1 \Rightarrow \texttt{true} \qquad A;\ e2 \Rightarrow v}{A;\ \texttt{if}\ e1\ \texttt{then}\ e2\ \texttt{else}\ e3 \Rightarrow v}$$

$$\frac{A;\ e1 \Rightarrow \texttt{false} \qquad A;\ e3 \Rightarrow v}{A;\ \texttt{if}\ e1\ \texttt{then}\ e2\ \texttt{else}\ e3 \Rightarrow v}$$

- Notice that only one branch is evaluated
  - A; `if eq0 0 then 3 else 4` ⇒ `3`
  - A; `if eq0 1 then 3 else 4` ⇒ `4`

Quiz 3

What is the derivation of the following judgment?

```
•; if eq0 3-2 then 5 else 10 ⇒ 10
```

```
(a)
•; 3 ⇒ 3    •; 2 ⇒ 2   3-2 is 1
-------------------------
•; eq0 3-2  ⇒  false        •; 10 ⇒ 10
-----------------------------------
•; if eq0 3-2 then 5 else 10  ⇒  10
```

```
(b)
3 ⇒ 3   2 ⇒ 2
3-2 is 1
---------------
eq0 3-2 ⇒ false         10 ⇒ 10
-------------------------------
if eq0 3-2 then 5 else 10 ⇒ 10
```

```
(c)
•; 3 ⇒ 3
•; 2 ⇒ 2
3-2 is 1
----------
•; 3-2 ⇒ 1    1 ≠ 0
------------------
•; eq0 3-2 ⇒ false     •; 10 ⇒ 10
-----------------------------------
•; if eq0 3-2 then 5 else 10 ⇒ 10
```

Quiz 3

What is the derivation of the following judgment?

```
•; if eq0 3-2 then 5 else 10 ⇒ 10
```

```
(a)
•; 3 ⇒ 3    •; 2 ⇒ 2   3-2 is 1
-------------------------
•; eq0 3-2  ⇒  false        •; 10 ⇒ 10
-----------------------------------
•; if eq0 3-2 then 5 else 10  ⇒  10
```

```
(b)
3 ⇒ 3   2 ⇒ 2
3-2 is 1
---------------
eq0 3-2 ⇒ false         10 ⇒ 10
-------------------------------
if eq0 3-2 then 5 else 10 ⇒ 10
```

```
(c)
•; 3 ⇒ 3
•; 2 ⇒ 2
3-2 is 1
----------
•; 3-2 ⇒ 1     1 ≠ 0
-------------------
•; eq0 3-2 ⇒ false      •; 10 ⇒ 10
-----------------------------------
•; if eq0 3-2 then 5 else 10 ⇒ 10
```

Updating the Interpreter

```
let rec eval env e =
  match e with
    Ident x -> lookup env x
  | Val v -> v
  | Plus (e1,e2) ->
     let Int n1 = eval env e1 in
     let Int n2 = eval env e2 in
     let n3 = n1+n2 in
     Int n3
  | Let (x,e1,e2) ->
     let v1 = eval env e1 in
     let env' = extend env x v1 in
     let v2 = eval env' e2 in v2
  | Eq0 e1 ->
     let Int n = eval env e1 in
     if n=0 then Bool true else Bool false
  | If (e1,e2,e3) ->
     let Bool b = eval env e1 in
     if b then eval env e2
     else eval env e3
```

Basically both rules for **eq0** in this one snippet

Both **if** rules here

Quick Look: Type Checking

- Inference rules can also be used to specify a program's static semantics
  - I.e., the rules for type checking
- We won't cover this in depth in this course, but here is a flavor.

- Types t ::= **bool** | **int**
- Judgment $\vdash e : t$ says e has type t
  - We define inference rules for this judgment, just as with the operational semantics

Some Type Checking Rules

- Boolean constants have type **`bool`**

$$\frac{}{\vdash \texttt{true} : \texttt{bool}} \qquad \frac{}{\vdash \texttt{false} : \texttt{bool}}$$

- Equality checking has type **`bool`** too
  - Assuming its target expression has type **`int`**

$$\frac{\vdash e : \texttt{int}}{\vdash \texttt{eq0}\ e : \texttt{bool}}$$

- Conditionals

$$\frac{\vdash e1 : \texttt{bool} \quad \vdash e2 : t \quad \vdash e3 : t}{\vdash \texttt{if}\ e1\ \texttt{then}\ e2\ \texttt{else}\ e3 : t}$$

Handling Binding

- What about the types of variables?
  - Taking inspiration from the environment-style operational semantics, what could you do?

- Change judgment to be G ⊢ ***e*** : ***t*** which says ***e*** *has type* ***t*** *under type environment* G
  - G is a map from variables ***x*** to types ***t***
    - Analogous to map A, maps vars to types, not values

- What would be the rules for **`let`**, and variables?

Type Checking with Binding

- Variable lookup

$$\frac{G(x) = t}{G \vdash x : t}$$

analogous to

$$\frac{A(x) = v}{A;\ x \Rightarrow v}$$

- Let binding

$$\frac{G \vdash e1 : t1 \qquad G, x{:}t1 \vdash e2 : t2}{G \vdash \texttt{let}\ x\ \texttt{=}\ e1\ \texttt{in}\ e2 : t2}$$

analogous to

$$\frac{A;\ e1 \Rightarrow v1 \qquad A, x{:}v1;\ e2 \Rightarrow v2}{A;\ \texttt{let}\ x\ \texttt{=}\ e1\ \texttt{in}\ e2 \Rightarrow v2}$$

Scaling up

- Operational semantics (and similarly styled typing rules) can handle full languages
  - With records, recursive variant types, objects, first-class functions, and more
- Provides a concise notation for explaining what a language does. Clearly shows:
  - Evaluation order
  - Call-by-value vs. call-by-name
  - Static scoping vs. dynamic scoping
  - ... We may look at more of these later