Distance Vector Routing

- Also known as Bellman-Ford or Ford-Fulkerson
  - original ARPANET routing algorithm
  - early versions of IPX and DECnet used it too
- Each router keeps a table of tuples about all other routers
  - outbound link to use to that router
  - metric (hops, etc.) to that router
  - routers also must know "distance" to each neighbor
- Every T sec., each router sends it table to its neighbors
  - each router then updates its table based on the new info
- Problems:
  - fast response to good news
  - slow response to bad news
    - takes max hops rounds to learn of a downed host
    - known as count-to-infinity problem

copyright 1997 - Jeffrey K. Hollingsworth

Link State Routing

- Used on the ARPANET after 1979
- Each Router:
  - computes metric to neighbors and sends to **every** other router
  - each router computes the shortest path based on received data
- Needs to estimate time to neighbor
  - best approach is send an **ECHO** packet and time response
- Distributing Info to other routers
  - each router may have a different view of the topology
  - simple idea: use flooding
  - refinements
    - use age sequence number to damp old packets
    - use acks to permit reliable delivery of routing info

copyright 1997 Jeffrey K. Hollingsworth

Hierarchical Routing

- Routing grows more complex with more routers
  - takes more space to store routing tables
  - requires more time to compute routes
  - uses more link bandwidth to update routes
- Solution:
  - divide the world into several hierarchies
    - Do I really care that router z at foo U just went down?
  - only store info about
    - your local area
    - how to get to higher up routers
  - optimal number of levels for an N router network is ln N
    - requires a total of e ln N entries per router

copyright 1997 Jeffrey K. Hollingsworth

Routing for Mobility

- Or What happens when computers move?
- Two types of mobility:
  - migratory: on the net in many locations but not while in motion
  - roaming: on the net while in motion
- Basic idea:
  - everyone has a home
    - you spend much of your time near home
    - when not at home, they know where to find you
  - home agents: know where you are (or that you are missing)
  - foreign agents: inform home agents of your location
    - informs users that future communication should be sent via them (this is a huge potential security hole)

copyright 1997 Jeffrey K. Hollingsworth

Broadcast Routing

- Sometimes information needs to go to everyone
  - routing updates in link-state
  - stock data, weather data, etc.
- sender iterates over all destinations
  - wastes bandwidth
  - sender must know who is interested
- flooding
  - see routing updates for issues
- multi-destination routing
  - routers support having multiple destinations
  - routers copy output packets to correct link(s)
- spanning tree
  - contains subset of graph with no loops
  - efficient use of bandwidth
  - requires info to be present in routers (but it is for link state)

copyright 1997 Jeffrey K. Hollingsworth

Routing Broadcast Traffic (cont.)

- Reverse path forwarding
  - check link a packet arrives on
  - if the inbound link is the one the router would use to the source, then
    - forward it out all other links
  - else
    - discard the packet
  - requires no special data sorted in each router



From: *Computer Networks*, 3rd Ed. by Andrew S. Tanenbaum, (c)1996 Prentice Hall.

copyright 1997 Jeffrey K. Hollingsworth

Multicast Routing

- Specify a (relatively) small list of hosts to receive traffic
  - may need to exchange traffic as a group
  - must create/destroy group
- Using spanning trees
  - prune links that are have no members of mulicast group
  - for distance-vector use a variation on reverse path forwarding
    - when a router gets a message it doesn't need it send a prune message back
    - recursively prunes back un-needed subnets
- core-based trees
  - one tree for group not one per group member
  - hosts send to "core" and it multicasts it out

copyright 1997 Jeffrey K. Hollingsworth